

N.

## NEW MEXICO OIL AND GAS CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

J. P. Cusack Inc.

Company or Operator

Moon "B"

Lease

Well No. 2 in E 1/2 NE 1/4 of Sec. 28, T. 18S

R. 38E N. M. P. M. Hobbs Field, Lea County.

Well is 330 feet south of the North line and 1120 feet west of the East line of Sec. 28

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is J. H. Moon, Address Tatum, New Mexico.

If Government land the permittee is, Address

The Lessee is J. P. Cusack Inc., Address Box 957, Ardmore, Okla.

Drilling commenced October 12, 1935 Drilling was completed April 22, 1936

Name of drilling contractor Noble Drilling Company, Address Tulsa, Oklahoma.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 4209 to 4285 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2	50#			226				
7"	22#			4133				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2		226	160	Halliburton		
8-3/8	7"	4133	750	"		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	5000	4-20-36		
			10000	4-22-36		

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 4221 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing 4-28, 1936

The production of the first 24 hours was 8488 barrels of fluid of which 100% was oil;

emulsion; % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

W. R. Sprouse, Driller Jerry Holt, Driller

Red Davis, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 12th

day of May, 1936

Mary Markay

Notary Public.

Ardmore, Oklahoma.

Name J. P. Cusack Inc.

Position Clerk

Representing J. P. Cusack Inc.

Company or Operator

My Commission expires 8-29-37

Address Box 957, Ardmore, Oklahoma.

DUPLICATE

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
40	40	40	Caliche
40	80	40	Sand and Gravel
80	90	10	Lime shells
90	200	110	Shells and water sand
200	210	10	Shells
210	227	17	Red Beds
227	729	502	" "
729	1030	301	Red beds and shells
1030	1387	357	Red beds
1387	1519	132	Red rock and shale
1519	1575	56	Red rock and gypsum
1575	1627	52	" " and shells & gypsum
1627	1675	48	" " shale & gypsum
1675	1709	34	" " " " "
1709	1751	42	" " " " Anhydrite
1751	1817	66	" " " " Gypsum
1817	1827	10	Anhydrite & salt
1827	1932	105	Shells and salt
1932	2162	230	Salt and Anhydrite
2162	2288	116	Salt
2288	2420	132	Salt & Anhydrite
2420	2561	141	Salt and Shells
2561	2725	164	Salt shale and shells
2725	2792	67	Anhydrite and salt streaks
2792	2903	111	Anhydrite
2903	2923	20	Gypsum & Anhydrite
2923	3018	95	Anhydrite
3018	3293	175	Anhydrite
3293	3307	14	Gypsum and Anhydrite
3307	3404	97	Anhydrite
3404	3427	23	Anhydrite
3427	3502	75	Anhydrite
3502	3532	30	Gray lime and anhydrite
3532	3555	23	Lime and Anhydrite
3555	3583	28	Anhydrite & lime shells
3583	3617	34	Anhydrite and streaks of lime
3617	3634	17	Lime and anhydrite
3634	3680	46	Anhydrite and lime
3680	3684	4	Anhydrite
3684	3745	61	Anhydrite and lime
3745	3761	16	Anhydrite and Gypsum
3761	3775	14	Anhydrite & gypsum and lime
3775	3794	19	Anhydrite and Gypsum
3794	3819	25	Anhydrite and Lime
3819	3834	15	Anhydrite, Gypsum and Lime
3834	3940	106	Broken lime and Anhy.
3940	3952	12	Hard Lime and Anhy.
3952	3970	18	Lime and Anhy
3970	4006	36	Lime
4006	4027	21	Gray lime
4027	4106	79	" "
4106	4116	10	Anhy. Broken gray & brown lime
4116	4225	9	Lime