

Submit this report in triplicate to the Ofi Conservation Commission or its proper agent within ten days after the Well specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERA-				
		REPORT ON I	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL	X	REPORT ON	PULLING OR OTHERWISI G CASING	E
REPORT ON RESULT OF TEST OF CASING SHUT-OFF			DEEPENING WELL	X
REPORT ON RESULT OF PLUGGING OF WELL		Run and Co	ement liner	
Hobbs, N	lev M		3-6-4	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:		Place	Date	
Following is a report on the work done and the results	obtain N T	ed under the head	ing noted above at the	
Shell Oil Company or Cylerator	¥	Lease	Well No.	in t
SW/4 of Sec. 28	, [ T	r. <u>18 S</u>	, R. <b>38 B</b> ,	N. M. P. M
Hobbs Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,Field,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FIEld,FFIEld,FFIEld,FIEld,FIEld,FFI	65			
GENERITED WITH LOO SACKS. Drille	d ca	tom at 4230	sepened from 4200 and top at 3918	t on A
emented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with On official gas oil ratio test w	d ce d 0. 500	tom at 4230 ment to 423 K, Perfore gallons, a	) and top at 3918 28 and tested lin ated liner from 4 and set packer at	and er wit 150 to 3801.
computed with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with 20 official gas oil ratio test w	d ce d C. 500 rell nch 0 77 cll	tom at 4230 ment to 422 K. Perfore gallons, a flowed 130 choke. Tub: Dil Company Company	) and top at 3918 28 and tested lin ated liner from 4 and set packer at	and or wit 150 to 3801. 3/10% pounds Engine Title
Computed with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with on official gas oil ratio test w 3.S. in 24 hours through 12/64-1 asing pressure 0, Gas oil ration Vitnessed by W.R. Bollinger Sh	d ce d 0. 500 e11 nch 077 e11 I is	tom at 4230 ment to 422 K. Perform gallons, a flowed 130 ghoke. Tub: Oil Company Company	) and top at 3918 28 and tested lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 v. Inc. Dist.	and or wit 150 to 3801. 3/10% pounds Engine Title
Semented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with 223, acidized perforations with 224, acidized perforations with 235, in 24 hours through 12/64-1 236, acidized perforations 236, acidized perforations with 236, acidized perforations with 236, acidized perforations with 236, acidized perforations with 236, acidized performance a	d ce d 0. 500 rell nch 077 ell is 6 Na	tom at 4230 ment to 422 K. Perfore gallons, a flowed 130 choke. Tub: <u>Oil Company</u> hereby swear or a true and correct.	) and top at 3918 28 and tested lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 v. Inc. Dist.	and or wit 150 to 3801. 3/10% pounds Engine Title
Semented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with 223, acidized perforations with 224, acidized perforations with 235, in 24 hours through 12/64-1 236, acidized perforations 236, acidized perforations with 236, acidized perforations with 236, acidized perforations with 236, acidized perforations with 236, acidized performance a	d ce d 0. 500 (ell nch 077 611 is 6 Na Po	tom at 4230 ment to 422 K. Perform gallons, a flowed 130 choke. Tub: Oil Company hereby swear or a true and correct. ame	) and top at 3918 28 and tos tod lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 , Inc. Dist. ffirm that the information p <i>hambert</i> it Superintendent 11 011 Company.	and or wit 150 to 3801. 3/10% pounds Engine Title
Semented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with 223, acidized perforations with 234, acidized perforations with 235, in 24 hours through 12/64-1 236, in 24 hours through 12/64-1 236, acidized performed by 236, acidized with 235, in 24 hours through 12/64-1 236, acidized performed by 236, acidized with 235, in 24 hours through 12/64-1 236, acidized with 12/64-1 236, acidized by 236, acidized with 236, acidized performed by 236, acidized with 236, acidized with 12/64-1 236, acidized with 12/64-1 236, acidized by 236, acidized with 12/64-1 236, acidized wit	d ce d 0. 500 (e11 nch 0 77 611 I is 6 Na Po Re	tom at 4230 ment to 422 K. Perfore gallons, a flowed 130 choke. Tub: 011 Company hereby swear or a true and correct. ame	b) and top at 3918 28 and tos tod lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 7. Inc. Dist. ffirm that the information p bhambert at Superintendent	and or wit 150 to 3801. 3/10% pounds Engine Title given above
Semented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with On official gas oil ratio test w 3.5. in 24 hours through 12/64-1 asing pressure 0. Gas oil ration Vitnessed by H.R. Bollinger Show Name Subscribed and sworn before me this 6th day of March 19.4	d ce d 0. 500 (e11 nch 0 77 611 I is 6 Na Po Re	tom at 4230 ment to 422 K. Perfore gallons, a flowed 130 choke. Tub: 011 Company hereby swear or a true and correct. ame	b) and top at 3918 28 and tos tod lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 r. Inc. Dist. ffirm that the information p Bhambert at Superintendent LI 011 Company, Company or Operator	and or wit 150 to 3801. 3/10% pounds Engine Title given above
Semented with 100 sacks. Drille 1000 pounds for 30 minutes. Hel 1223, acidized perforations with 223, acidized perforations with 234, acidized perforations with 24, acidized p	d ce d 0. 500 (e11 nch 0 77 611 I is 6 Na Po Re	tom at 4230 ment to 422 K. Perfore gallons, a flowed 130 choke. Tub: 011 Company hereby swear or a true and correct. ame	b) and top at 3918 28 and tos tod lin ated liner from 4 and set packer at barrels oil cut ing pressure 350 r. Inc. Dist. ffirm that the information p Bhambert at Superintendent LI 011 Company, Company or Operator	and or wit 150 to 3801. 3/10% pounds Engine Title given above

· . • 

. 

and the second second

 $\frac{1}{2} \sum_{i=1}^{n} \frac{1}{2} \sum_{i=1}^{n} \frac{1$ 

andro an Andro andr Andro andr

教学科学会会 発展する ないてい 大口 経営学 しょういち たいしょうしょう

가 가지 않는 것을 알려요. 정말 것을 가지 않는 것을 이 것을 가지 않는 것을 알려야 하는 것을 가지 않는 것을 것을 가지 않는 것을 가지 않는 것을 가지 않는 것을 가지 않는 것을 알려 있다. 것을 같은 것을 알려 있는 것을 같은 것을 알려 있다. 같이 한 것을 하는 것을 것을 하는 것을 알려야 하는 것을 같은 것을 하는 것을 같은 것을 알려야 한 것을 같은 것을 같은 것을 같은 것을 같은 것을 같이 같은 것을 같이 같은 것을 같이 없다. 것을 같이 않 

24. A state of the second sec second sec