

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, Hobbs, N.M. The work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

February 24, 1959

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

**Sinclair Oil & Gas Company** **W.D. Grimes** Well No. **2** in **F**  
(Company or Operator) (Unit)  
**SE 1/4 NW 1/4 of Sec. 28**, T. **18N**, R. **38E**, NMPM., **Hobbs** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

PROPOSE TO Plug and Abandon Well, as follows:

(Offset operators  
have been notified  
of this intention  
to plug and abandon)

Cut 3" OD Tubing off at 3135' or below if possible.

Set Cast Iron Drillable Retainer just above the stuck tubing and squeeze  
open hole section 3974'-4223' with approximately 250 sacks cement.

Cut 6-5/8" OD Casing at approximately 3000' and pull.

Spot 300 sacks cement from 2350'-3100'.

Spot 25 sack cement plug in the top of 10-3/4" Casing and bottom of cellar,  
with 4" regulation marker set 4' above surface. Fill cellar, clean and  
level loss tion.

16" OD Casing set at 223' with 200 sacks cement.

10-3/4" OD Casing set at 2710' with 700 sacks cement.

6-5/8" OD Casing set at 3974' with 250 sacks cement.

3" OD Tubing set at 4235' - stuck on bottom &amp; split at 3135' f/surface

Approved.....  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy *[Signature]*  
TitleBy *[Signature]*Position **Dist. Supt.**

Send Communications regarding well to:

Name **C.C. Salter**Address **520 E Broadway, Hobbs, N.M.**

Orig &amp; 2cc: OCC; cc:FHR,HFD,File