

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. A1469

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFINISH OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT TO DRILL OR REFINISH FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Date
2. Name of Operator Amerada Hess Corporation	8. Form or Lease Name State "B"
3. Address of Operator Drawer "D", Monument, New Mexico 88265	9. Well No. 5
4. Location of well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>29</u> TOWNSHIP <u>18-S</u> RANGE <u>38-E</u> N.M.P.M.	10. Well and Pool, or Wildcat Hobbs Bowers Seven Rivers
11. Elevation (Show whether DF, RT, GR, etc.) 3655' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☒
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR FILLER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 15 - 22, 1981

Pulled rods, pump & tbq.. Ran RBP & pkr.. Set BP at 2266' w/pkr. set at 2203'. Tested RBP w/1000# pressure. Held OK. Loaded annulus & press. to 1000#. Held OK. Recovered pkr.. Spot 4 sks. sand on BP. Perf. 5-1/2" csg. w/4 shots fr. 1680' to 1682'. Established injection thru perfs.. Ran E-Z drill retainer, set at 1573'. Cement squeezed 5-1/2" csg. perf. 1680' to 1682' w/ total of 370 sks. cement. Left 15 sks. cement below retainer, 6 sks. above retainer, circ. 5 sks. to pit & reversed out 2 sks., squeezed 5 sks. into formation. WOC. Ran bit & drld. retainer & cement inside 5-1/2" csg. fr. 1573' to 1732'. Circ. hole clean & tested 5-1/2" csg. w/850# press. for 30 min.. Held OK. Washed sand off BP & recovered BP. Re-ran tbq., pump & rods & resumed pumping.

Test of July 1, 1981. Pumped 4 b.o. in 24 hrs. on 9-34" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R. E. Wheeler</u>	TITLE <u>Production Clerk</u>	DATE <u>8-5-81</u>
APPROVED BY <u>Jerry Newton</u>	TITLE <u>Dr. L. Sapp</u>	DATE <u>AUG 7 1981</u>
CONDITIONS OF APPROVAL, IF ANY:		