


N.

NEW MEXICO STATE LAND OFFICE
SANTA FE, NEW MEXICODEPARTMENT OF THE STATE GEOLOGIST
(State Deaf, Dumb and Blind School Land)
WELL RECORDMail to State Geologist, Santa Fe, New Mexico, not more than ten days
after completion of well. Indicate questionable data by fol-
lowing it with (?). Submit in duplicate.

Company **Continental Oil Company** Address **Hobbs, N. Mexico**
 Send correspondence to **H.B. Hurley** Address **Box 787 Hobbs, N. Mexico**
State A Well No. **I** in **S.E. 1/4** of Sec. **29**, T. **18 S**,
 R. **38 E**, N. M. P. M., **Hobbs** Oil Field **Lea** County.
 If State land the oil and gas lease is No. **1148** Assignment No. _____
 If patented land the owner is _____ Address _____
 The lessee is **Continental Oil Company** Address **Ponca City, Okla**
 If not state or patented land, give status _____
 Drilling commenced **July 6** 19 **30** Drilling was completed **Sept 24** 19 **30**
 Name of drilling contractor **Carey & Mitchell** Address **Wichita Falls, Texas**
 Elevation above sea level at top of casing **3645.22** feet.
 The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from **3161** to **3170** No. 4, from **3639** to **3660**
 No. 2, from **3340** to **3360** No. 5, from **4000** to **4010**
 No. 3, from **3400** to **3420** No. 6, from **4070** to **4178**

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATED		PURPOSE
							FROM	TO	
12 1/2	50	8	Natl.	234	T.P.				
9 5/8	40	8	"	2742	T.P.				
7	24	10	"	3929	T.P.				

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2	234	170	Halliburton		
9 5/8	2742	500	"		
7	3929	300	"		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
 Adapters—Material _____ Size _____

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from **0** feet to **4178** feet, and from _____ feet to _____ feet
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **Sept. 28**, 19 **30**
 The production of the first **24** hours was **701.1** barrels of fluid of which **99.2** % was oil; **.6** %
 emulsion; **.2** % water; and _____ % sediment. Gravity, Be _____
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. **1250**

EMPLOYES

Ted Russel, Driller **John Long**, Driller
C.L. Sullivan, Driller **O.W. Sullivan**, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work
 done on it so far as can be determined from available records.

Subscribed and sworn to before me this **Fourth** day of **October**, 19 **30** Name **G.A. Carpenter**
 Position **District Clerk**
 Representing **Continental Oil Company**
 Notary Public. _____
 My commission expires **Jan 13**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	18	18	(Cellar)
18	20	2	Caliche
20	60	40	Sand
60	65	5	Sand Rock
65	138	73	Hard Sand
138	215	77	Soft Sand
215	246	31	Red Rock
246	254	8	Sand
254	400	46	Red Rock
400	595	195	Red Rock & Sand
595	1050	455	Sand & Shells
1050	1290	240	Red Rock
1290	1320	30	Hard Sand
1320	1421	101	Shells
1421	1448	27	Hard Sand
1448	1452	4	Sand
1452	1468	16	Red Rock
1468	1531	63	Hard Sand
1531	1538	27	Anhydrite
1538	1623	65	Anhydrite & Red Rock
1623	1638	15	Red Rock
1638	1654	16	Anhydrite
1654	1668	14	Anhydrite & Red Rock
1668	1669	4	Salt
1669	1792	123	Anhydrite & Salt
1792	1900	108	Anhydrite, Salt & Potash
1900	2574	674	Anhydrite & Salt
2574	2742	168	Anhydrite
2742	3847	1105	Lime (Oil at 3161, 3340 to 3350, 3360 to 3370)
3847	3871	24	Anhydrite & Lime
3871	3881	10	Brown Lime
3881	3900	19	Anhydrite & Lime
3900	3961	61	Gray Sandy Lime
3961	3970	9	Brown Lime
3970	3987	17	Gray Sandy Lime
3987	4010	23	Brown Lime
4010	4037	27	Hard Gray Lime
4037	4045	8	Brown Lime
4045	4052	7	White Lime
4052	4070	18	Brown Lime
4070	4080	10	Gray Lime
4080	4025	45	Hard Brown Lime
4025	4178	153	Brown Lime with hard & soft streaks

Well completed by setting and connecting
4138 feet 3"-9.30 lb. 10 thd. API National
Seamless ext. upset tubing.