
NEW MEXICO OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO MISCELLANEOUS NOTICES



advisable, or the rejection by the Commission or agen ed, and work should not begin until approval is obtain the Commission.	ich will be given the approval, with any modifications t, of the plan submitted. The plan as approved should ned See additional instructions in the Rules and Regu	consider be follo llations
- · · · · · · · · · · · · · · · · · · ·	f notice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
	Hobbs New Mexico April 11,	1947
	Place Date	_/-/
OIL CONSERVATION COMMISSION,		
Santa Fe, New Mexico.		
Gentlemen:		
Following is a notice of intention to do certain work a	as described below at the	
Continental Oil Company State	Well No. 6 in	SW/L
Company or Operator Lease	· · · · · · · · · · · · · · · · · · ·	/ -
of Sec. 29 , T. 18-3 , R. 38-K	, N. M. P. M., Bowers	Fie
Les Country		
County.		
- County.		
FULL DETAILS OF I	PROPOSED PLAN OF WORK	
FULL DETAILS OF I	PROPOSED PLAN OF WORK LES AND REGULATIONS OF THE COMMISSION	
FULL DETAILS OF I		
FULL DETAILS OF I	LES AND REGULATIONS OF THE COMMISSION	Who o
FULL DETAILS OF I		Was s
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF I	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL Well was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	On April 10, 1947, 12 3/4" OD casing	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	On April 10, 1947, 12 3/4" OD casing the circulated. Test for water shut-one	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUI #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cem made on April 11, 1947.	CONTINENTAL OIL COMPANY Company or Operator	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	On April 10, 1947, 12 3/4" OD casing the circulated. Test for water shut-of continental oil company	
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	CONTINENTAL OIL COMPANY Company or Operator By	ee wi
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	CONTINENTAL OIL COMPANY Company or Operator By Position District Superintender	ff wi
FULL DETAILS OF F FOLLOW INSTRUCTIONS IN THE RUL #ell was drilled to 265° in redbed. 260° and cemented with 200 sacks. Cemented on April 11, 1947.	CONTINENTAL OIL COMPANY Company or Operator By	ff wi

Title

Name . Box CC Address

Hobbs, New Mexico