

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	<b>X</b>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Royalty, Texas  
(Place)

March 27, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Standard Oil Company of Texas

State 1-29 Well No. 2 in SE (Unit)  
(Company or Operator)  
SW 1/4 SE 29 of Sec. 18-S, T. 38-E, R. NMPM, Bowers Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

To repair casing leak. Details of proposed work on attachment.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION  
By E. J. Fischer  
Title.....

STANDARD OIL COMPANY OF TEXAS  
Company or Operator

By J. M. McMahan  
J. M. McMahan  
Position District Engineer  
Send Communications regarding well to:

Name STANDARD OIL COMPANY OF TEXAS  
Address Bin "B", Royalty, Texas

FULL DETAILS OF PROPOSED PLAN OF WORK

Present Condition of Well:

Temporarily abandoned August, 1956, for economic reasons.

T.D. 4171', PBTD 3627'

Casing: 13 3/8" at 225' with 150 sacks cement

9 5/8" at 2822' with 725 sacks cement

7" at 3951' with 300 sacks cement

Casing Perforations: 3155-3175'

Proposed Work:

It is proposed to repair leaks in the 7" casing to comply with O.C.C. rules regarding underground waste in the following manner:

1. Set bridge plug at 3070' and load hole with water
2. Close in 7" casing and breakdown with water through 9 5/8" casing.
3. Squeeze cement down 9 5/8" casing using sufficient cement to fill 7" - 9 5/8" annulus plus 100 sacks. Depending on initial breakdown pressure, squeeze until satisfactory volume has been squeezed or until satisfactory pressure has been reached. If pressure does not increase, shut-in well without displacing cement.
4. Wait on cement 24 hours, bleed pressure and shut-in for pressure build up test.
5. If pressure has not been excluded, plug well by spotting cement plugs in 7" casing.

THE HISTORY OF THE

THE HISTORY OF THE

THE HISTORY OF THE

THE HISTORY OF THE

THE HISTORY OF THE

THE HISTORY OF THE