


WELL NO. 1  
(1000-1000)



(U.S. DEPARTMENT OF THE INTERIOR)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

WELL NO. 1, 1000-1000

LEASE NO. 032233 (a)

WELL NO. 1, 1000-1000

SUMMARY NOTES AND REPORTS ON WELLS

|                       |                                    |
|-----------------------|------------------------------------|
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |
| WELL NO. 1, 1000-1000 | SUMMARY NOTES AND REPORTS ON WELLS |

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

DETAILS OF WORK

(NOTE: ALL INFORMATION ON THIS FORM IS TO BE USED FOR THE PURPOSES OF THE GEOLOGICAL SURVEY AND NOT FOR THE PURPOSES OF THE BUREAU OF LAND MANAGEMENT.)

1. Bore Queen formation 3736-3741', tested water after treating with 500 gal LSTNE acid
2. Squeeze cemented perils 3736-3741' w/40 ex regular neat cement - 100 cement 3686' 0.30.
3. Bore Queen Bore Queen Sand 3222-3227' w/2 sets/ft.
4. Treated w/500 gal LSTNE acid - Swabbed dry.
5. Treated perils 3222-3227' w/10,000 gal Hubble Frac Oil and 20,000 sand. Swabbed and pumped dry, approx 20 barrels frac oil - unable to recover.

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000

WELL NO. 1, 1000-1000