

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces, N.M.
Lease No. 032233-A
Unit _____

B.A. Bowers "A" - Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REPAIRING OR REPAIR.....	X
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, Sept. 20, 1949

Well No. 9 is located 2310 ft. from N line and 990 ft. from W line of sec. 29
W/2 of W/2 of Sec. 29 13-5 38-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Hobbs Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Loaded tubing with water, conditioned mud and drilled out Baker Production Packer. Worked hole to bottom at 4231'. Tested well and swabbed 100% water. Set packer at 4120'. Swabbed and tested 24 hours making 90% water. Set packer at 4140'. Swabbed 8 bbls. per hour, 60% water. Swabbed 11 hours making 7 barrels per hour, 25% water. Set packer at 4100' and 3875'. On 21 hour flow test well made 18 bbls. per hour, 50% fresh water and drilling mud. In 24 hours flowed 30 bbls. per hour, 45% water and drilling mud. Salt content 6000 PPM. Tested well 8 hours and made 35 bbls. per hour, 40% water. Set retainer at 4100' and cemented with 50 sacks Lone Star Cement under retainer. Set packer at 3880'. Cleaned well to pits making 50% water. Tested well for 12 hours on 1/2" choke at rate of 25 barrels per hour, 40% fresh water. Tubing pressure 100%. Plug back depth 4100'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining Co.

Address Box 1600
Midland, Texas

By [Signature]
 Title Asst. Div. Superintendent