

10-11-56
(25-1055)

X			

(SUBMIT IN TRIPPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

032233-A
UNIT

B. A. Bowers "A" Federal
OCT 30 1956

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		Subsequent Report of Setting Liner	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

AMENDED NOTICE

Hobbs, New Mexico, October 29, 1956

WELL NO. 4-10 IS LOCATED 2310 FT. FROM {S} LINE AND 990 FT. FROM {W} LINE OF SEC. 29
 NW 1/4 of SW 1/4 Sec. 29 13 S 38E
 (1/4 SEC. AND SEC. NO.) (TWP.) (RANGE) (MERIDIAN)
 Hobbs Lea New Mexico
 (FIELD) (COUNTY OR SUBDIVISION) (STATE OR TERRITORY)

THE ELEVATION OF THE DERRICK FLOOR ABOVE SEA LEVEL IS _____ FT.

DETAILS OF WORK

(STATE NAMES OF AND EXPERTED DEPTHS TO OBJECTIVE SANDS; SHOW SIZES, WEIGHTS, AND LENGTHS OF PROPOSED JOBS. INDICATE MIDDING JOBS, CEMENTING POINTS, AND ALL OTHER IMPORTANT PROPOSED WORK.)

Drilled Baker bridge plug out at 3910'. Worked packer to bottom of hole at 4220'. Ran and set 348.53' of 5" liner at 4220'. Top of liner at 3872'. Cemented over w/50 sx. Lone Star cement. Cement in place at 9:00 PM 6-27-56. Perforated liner w/1 jet shots per foot from 4180-4192. Ran 2" 6g. w/Baker full open cementer. Ran 133 joints 2" tubing 4156' set at 4154'. Washed perforations with 250 gallons 15% LT acid. Put 2000# on casing annulus. Maximum pressure on tbg. 6000#. Killed well with fresh water. Released Baker cementer & installed Xmas Tree. Reset Baker FBRC at 4168'. Acidized down tbg. w/500 gallons special LT acid. Minimum pressure 800#, maximum pressure 950#. Flushed with 16 bbls. oil. Well completed as flowing oil well thru perforations in 5" liner from 4180-4192'.

On a 24 hour test on July 5, 1956 the well produced 79 barrels of pipe line oil, 8 barrels of water and 147 Mcf of gas per day.

I UNDERSTAND THAT THIS PLAN OF WORK MUST RECEIVE APPROVAL IN WRITING BY THE GEOLOGICAL SURVEY BEFORE OPERATIONS MAY BE COMMENCED.

COMPANY Humble Oil & Refining Company

ADDRESS Box 7347

Hobbs, New Mexico

By R. K. Jenkins

TITLE Agent