



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces, N. M.

Lease No. 03233-A

Unit \_\_\_\_\_

B. A. Jones "A" Federal

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF <del>WATER SHUT-OFF</del> OR ACIDIZING.....	<b>X</b>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<b>X</b>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 27, 1956

Well No. A-20 is located 2310 ft. from N line and 990 ft. from W line of sec. 29

N 1/4 of SW 1/4 Sec 29 18 S 38 E  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Hobbs Las New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled Baker bridge plug out at 3910. Worked packer to bottom of hole at 4220. Ran and set 348.53' of 5" liner at 4220. Top of liner at 3872. Cemented same w/90 sz Long Star. Perforated liner w/4 jet shots per foot from 4180-4192. Washed perf w/250 gallons 15% LT acid. Acidized down tubing w/500 gallons special LT acid.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining Company

Address Box 2347

Hobbs, New Mexico

By [Signature]

Title gent