X

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	عدا	Cruces
Lease No)3223.	3-A
Unit B.	. Bo	mers a
(Pe	odora	1)

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES A	
IOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
OTICE OF INTENTION TO TEST WATER SHUT-OFF	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSECUENT REPORT OF RE-DRILLING OR REPAIR.
OTICE OF INTENTION TO RESPONDE ON RESTANDANCE OF INTENTION TO SHOOT OR ACIDIZE	
OTICE OF INTENTION TO SHOOT OR ACTURED	
IOTICE OF INTENTION TO POLL OR ALTER CASHIO	
IOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MAI	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	February 1, 1956
ell No. 7 is located 2770 ft. fro	om. $\{S\}$ line and 330 ft. from $\{W\}$ line of sec. 29
1/4 of Nu 1/4 of Sec 29 18-S (½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
America	Les New Mexico
(Field) (Count	ty or Subdivision) (State or Territory)
	level isft. *AILS OF WORK *r sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work)
rate names of and expected depths to objective sands; show ing points, and a second Bowers A 7 was abandoned a 15 foot cement plug from 3090 at 3090 feet. 10 foot cement plug from 10 feet. 10 foot cement plug from 10 feet. 10 fact cement plug from 10 feet. 11 Factor placed as required by R	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work) as follows: to 3075 fact on cast iron bridge plug set
rederal Bowers A 7 was abandoned a 15 foot cement plug from 3090 at 3090 feet. 10 foot cement plug from 10 feet. 1. 10 foot cement plug from 10 feet. 1. 10 foot cement plug from 10 feet. 1. Aarker placed as required by a sork was done on January 17, 1956. I understand that this plan of work must receive approve	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, comes all other important proposed work) Is follows: to 3075 feet on cast iron bridge plug set let to surface. Here Mexico II Conservation Commission.
Tederal Bowers A 7 was abandoned a 15 foot cement plug from 3090 at 3090 feet. 10 foot cement plug from 10 feet. 11 feet placed as required by feet fork was done on January 17, 1956. 1 understand that this plan of work must receive approve for feet for feet for feet for feet feet feet feet feet feet feet fee	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, comes all other important proposed work) Is follows: to 3075 feet on cast iron bridge plug set oet to surface. Here Mexico II Conservation Commission.
rederal Bowers A 7 was abandoned a 15 foot cement plug from 3090 at 3090 feet. 1. 10 foot cement plug from 10 feet. 2. 10 foot cement plug from 10 feet. 3. Casing filled with water. 3. Marker placed as required by Marker placed by Marker placed as required by Marker placed as required by Marker placed as required by Marker placed	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, comes all other important proposed work) Is follows: to 3075 feet on cast iron bridge plug set oet to surface. Here Mexico II Conservation Commission.
deral Bowers A 7 was abandoned a 15 foot cament plug from 3090 at 3090 feet. 10 foot cament plug from 10 feet. Casing filled with water. Marker placed as required by a sork was done on January 17, 1956 I understand that this plan of work must receive approve the company humble will a Refining and Address Box 2347	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work) Is follows: to 2075 feet on cast iron bridge plug set net to surface. New Mexico (11 Conservation Commission. al in writing by the Geological Survey before operations may be commenced. Company
ederal Bowers A 7 was abandoned a 15 foot cement plug from 3090 at 3090 feet. 10 foot cement plug from 10 feet. Casing filled with water. Marker placed as required by a fork was done on January 17, 1956 I understand that this plan of work must receive approve	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work) Is follows: to 2075 feet on cast iron bridge plug set net to surface. New Mexico (11 Conservation Commission. al in writing by the Geological Survey before operations may be commenced. Company
deral Bowers A 7 was abandoned a 15 foot cament plug from 3090 at 3090 feet. 10 foot cament plug from 10 feet. Casing filled with water. Marker placed as required by a sork was done on January 17, 1956 I understand that this plan of work must receive approve the company humble will a Refining and Address Box 2347	AILS OF WORK raizes, weights, and lengths of proposed casings; indicate mudding jobs, come all other important proposed work) a follows: to 3075 fact on cast iron bridge plug set let to surface. lew Mexico all Conservation Commission. By Man Rayman Tall.