

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY B. A. POWER "W" - FEDERAL

CORRECTED DATE OF APPLICATION TO DRILL

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	☐	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	☐	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	☐	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	☐	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	☐	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	☐	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, September 17, 1948

Well No. 1-AE is located 300 ft. from $\begin{matrix} N \\ \times \end{matrix}$ line and 600 ft. from $\begin{matrix} W \\ \times \end{matrix}$ line of sec. 35

North of the 1/4 of sec. 29 18-38-E

Now in Lea New Mexico

The elevation of the derrick floor above sea level is 3650 ft.

DETAILS OF WORK

(State names of and expected dip to objective sands; show sizes, weights, and lengths of proposed casing and center tubing jobs, cementing points, and all other important proposed work)

CASING PROGRAM

SIZE OF PIPE	SIZE OF CASING	WEIGHT	NOMINAL LENGTH-FT.	DEPTH	LENGTH OR CEMENTED	SHOBS OR JOINTS	METHOD OF CEMENTING
11"	8-5/8"	28#	Nov.	500'	Cemented	200 sx.	Halliburton
8-5/8"	6-1/2"	24#	"	3250'	"	1000 sx.	"

The 8-5/8" casing will be cemented to the surface. The cement around the 6-1/2" casing will extend into the 8-5/8" surface casing.

Intend to test lower sand at an approximate depth of 3250'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining Company

Address 1001 18th, Midland, Texas

By.

Title Asst. Division Superintendent