(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

3. 3. 30 444

| Unit | 032233-A |
|------|----------|
| | |
| | |

SUNDRY NOTICES AND REPORTS ON WELLS

| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY |
|---|---|
| (INDICATE ABOVE BY CHECK MAR | K NATURE OF REPORT, NOTICE, OR OTHER DATA) |

| | | Midland, | Texas | September 30, | 19.48 | |
|------------------------------|-------------------------|-------------------|-----------------|--|-------|--|
| Well No. is located | 660 | ft. from N line a | nd 660 f | t. from $\left\{\begin{matrix} \mathbf{XXX} \\ \mathbf{E} \\ \mathbf{W} \end{matrix}\right\}$ line of sec. | 29 | |
| Na/4 of Na/4 of Sec. 29 | 18-5 | 38-E | | | | |
| (¼ Sec. and Sec. No.) Boners | (Twp.) | (Range) | (Meri | new Yexico | | |
| (Field) | (County or Subdivision) | | | (State or Territory) | | |
| | | 3650 | _ | | | |

The elevation of the derrick floor above sea level is _____ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 8-5/8" Casing as Pollows:

| <u>51.20</u> | Asount | eight | Jot At | <u>Formation</u> | of Well | No. Sacke Make Cement | Botton |
|--------------|--------|-------|--------|------------------|---------|--------------------------|------------------------------|
| 8-5/8# | 2481 | 24.69 | 2591 | Red Bed | 2661 | 150 sx. Common | 9140 A.M. 9-29 -48 |

Halliburt n Method Used. Circulated out 25 sacks excess coment. Will test casing with 800% at 9:40 A.M., 9-30-48.

Widland, Texas

By

Title

Asst. Division Superintendent