

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Midland, Texas

October 19, 1942

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Co. **W. D. Grimes** Well No. **1** in the
Company or Operator Lease
NE/4 of Sec. **25 29** T. **18-S** R. **37-E**, N. M. P. M.,
Hobbs Field, **Lea** County

The dates of this work were as follows: **July 11, 1942 to October 16, 1942**

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **7-15-42 & 10-19-42** 19
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Pulled 3" tubing and put on blowout preventer. Cleaned well out to bottom at 4223'. Ran 279' of 5-1/2" blank liner set at 4220' with 30 sacks Trinity cement. Swabbed hole dry to top of 5-1/2" liner at 3491'. Liner tested OK. Drilled plug & tested formation OK with 1200#. Deepened well to 4250'. Treated well with 1000 gallons Dowell acid from 4233' to 4250'. Swabbed well 8 hrs. Pulled tubing & ran 3 - 2" perforated couplings spaced at 1530', 2298' and 3258'. Unloaded well with gas. Made 26 bbls. oil in 24 hrs. by gas lift. 1% BS&W.

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn to before me this **19th**day of **Oct.** 19 **42**

W. D. Grimes
Notary Public

My Commission expires **6-1-43**

I hereby swear or affirm that the information given above is true and correct.

Name *W. D. Grimes*Position **Division Superintendent**Representing **Humble Oil & Refining Co.**
Company or OperatorAddress **Box 1600, Midland, Texas**

Remarks:

Roy J. H. H. H.
Name _____
Title _____

