

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION 12 1951

MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
OIL CONSERVATION COMMISSION  
HOBBES-OFFICE  
Form C-103

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

MAY 1 1970, STANDARD C"  
COMPANY OF TEXAS IS CHANG-  
ING ITS OPERATING NAME TO  
CHEVRON OIL COMPANY.

July 12, 1951

Hobbs, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Associated Oil Company W.D. Grimes Well No. 2 in the  
Company or Operator Lease  
37 SE NE of Sec. 29 T. 18-S R. 38-E, N. M. P. M.,  
Bowers Pool Lea County.

The dates of this work were as follows: June 28, 1951 - July 3, 1951

Notice of intention to do the work was ~~CROSS OUT~~ submitted on Form C-102 on June 26, 1951, 19  
and approval of the proposed plan was ~~CROSS OUT~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Tubing was run in this well and the hole circulated with 10#/gal mud. A cement plug(15 sacks) was spotted at the bottom in the 5 1/2" casing, and the 5 1/2" casing shot off at 2030'. The 7" casing was shot off simultaneously with the 5 1/2" casing. After recovery of the 5 1/2" and 7" casing (2030' of each), a 25 sack cement plug was spotted 2030' in the 9 5/8" casing and this string shot off 1200'. After recovering 1200' of this string a 10 sack cement plug was then laid at the surface in the 15 1/2" casing with a 4" marker pipe rising 4' above the ground level according to Commission regulations.

- Orig., lcc - OCC
- lcc - Tulsa
- lcc - Houston
- lcc - Midland
- lcc - file

Witnessed by E. A. Hogue Tide Water Associated Oil Company Head Roustabout  
Name Company Title

APPROVED:  
OIL CONSERVATION COMMISSION

*Notary Public*  
Oil & Gas Inspector  
Name  
Title

JUL 13 1951

Date

19.

I hereby swear or affirm that the information given above is true and correct.

Name H. P. Shackelford  
Position District Foreman

Representing Tide Water Associated Oil Company  
Company or Operator

Address Drawer KK, Hobbs, New Mexico