

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 8 1946
REGISTERED

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 7th, 1946

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Associated Oil Co., W.D. Grimes Well No. 3 in the

NE/4 of Sec. 29, T. 18-S, R. 38-E, N. M. P. M.,
Hobbs Field, Lea County.

The dates of this work were as follows: October 13th to November 1st, 1946

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on October 16th, 1946and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Killed well and pulled tubing, tested 7"OD casing and found holes from 368' to 403', squeezed holes with 120 sacks cement, drilled out and tested with 1000# pressure, held OK. Deepened hole from 4190' to 4230' Gr. meas. Ran 526.93' of 5-1/2"OD 15.5# liner, set at one ft. off bottom and cemented with 120 sacks cement; drilled out cement to 4228' and perforated with 8 shots per foot from 4202' to 4225' and acidized with 500 gallons of Chemical Process 15% acid. Swabbed well in and cleaned up. Production test was 190.78 bbls oil in 22 hrs 45 min., GOR 818/1, mud .2 of 1%.

Witnessed by H.G. Nesberry, Tide Water Associated Oil Co., Foreman
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

8th day of Nov., 1946

Name H. Nesberry

Position Foreman

Representing Tide Water Associated Oil Co.
Company or Operator

My commission expires Oct. 24, 1949

Address Drawer KK, Hobbs, New Mexico

Remarks:

APPROVED

Date NOV 1946

Name
Oil & Gas Inspector
Title