

NEW MEXICO STATE LAND OFFICE
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Hobbs N. Mex., Oct. 3, 1930

Mr. R.L. Halley,
Carlsbad, N.M.
State Geologist,
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in Grimes
Well No. 3 in NE4 of Sec. 29, T. 18-s, R. 38-s,
N. M. P. M., Hobbs Oil Field Lea County,
on Sept. 4, 1930 7"OD 24 1/2 lb. casing was ~~XXXXXX~~ cemented in Lime
formation at a depth of 3900' feet on Sept. 28 1930
400 sacks of El Toro Oil Well cement were used.

The method used in placing the cement was as follows:

Halliburton Process.

Fluid level will be bailed to a depth of 2500' feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows Humble Oil Co. Continental Oil Co.,
Amerada Oil Co. California Oil Co., Shell Pet Co., Prairie Oil & Gas Co.

Additional information:

**Cemented 9-5/8" OD Casing at 2720' w/ 600 sacks of
El Toro Oil Well Cement by Halliburton Process.**

Approved 10/6 30

Except as follows:

Sincerely yours,

TIDAL OIL COMPANY

Company or Operator.

By J.C. Wade

Position Dist. Foreman

Send communication regarding well to

Name TIDAL OIL COMPANY
W.T. WAGGONER BUILDING

Address FT. WORTH, TEXAS

R.L. Halley
State Geologist or Oil and Gas Inspector.

John
3-30-87

11/19/81
Mount Bond Log