

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

July 5th, 1950

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Tide Water Associated Oil Co. W.D. Grimes Well No. 5 in the

Company or Operator NE/4 of Sec. 29, T. 18-S, R. 38-E, N. M. P. M.,  
Hobbs Field, Lea County.

The dates of this work were as follows: Started on 6/19/50 and completed on 6/29/50

Notice of intention to do the work was (was not) submitted on Form C-102 on June 19th 1950  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was circulated with 10# mud and 60 sack cement plug placed from T.D. of 4,196' to 3,896', shot off and pulled 1,635' of 7" casing, placed 20 sack cement plug in 9-5/8" casing from 1,425' to 1,375', shot off and pulled 1,022' of 9-5/8". Placed 20 sack cement plug in top of 13"OD casing, and sweeted 4" pipe marker. The following amounts of casing was left in hole:  
214' of 13"OD casing (All left in)  
1,694' of 9-5/8" OD casing  
2,276' of 7"OD casing

This work was done by Hobbs Pipe & Supply Co., Hobbs, New Mexico

Witnessed by H. W. Arbery TIDE WATER ASSOCIATED OIL CO. Foreman  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

6th day of July 1950

I hereby swear or affirm that the information given above is true and correct.

Name H. W. Arbery

Position Foreman

Representing Tide Water Associated Oil Company  
Company or Operator

Notary Public

My commission expires \_\_\_\_\_ Commission Expires June 11, 1952

Address \_\_\_\_\_

Remarks:

APPROVED

Date JUL 6 1950

H. W. Arbery  
TIDE WATER ASSOCIATED OIL CO.  
Name

Title