


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on setting Casing	X

March 7, 1947 Date Monument, New Mexico Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amer. de Petroleum Corporation H. L. McKinley Well No. 6 in the
Company or Operator Lease

NE 1/4 NW 1/4 of Sec. 30 T. 18S R. 38E, N. M. P. M.,
Bowers Field, Lea County.

The dates of this work were as follows: March 6, 1947

Notice of intention to do the work was (crossed out) submitted on Form C-102 on March 6, 1947
and approval of the proposed plan (crossed out) (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

425' Total Depth Red Bed. Ran 2 jts 7 5/8" OD 17.9#, Armaco Slip joint Spiral Weld, 6 jts 7 5/8" OD 24.4, H-40, R-3, 8 RT, National Tube and 3 jts 7 5/8" OD 26.40#, J-55, R-2, 8 RT National Tube Seamless Steel Casing, total of 11 joints and set at 416' and cemented with 150 Sacks OK Common and 50 Sacks Trinity High Early Strength Cement and plug pumped to 399' with a final pressure of 300# at 10:30PM March 6, 1947, cement circulated.

Witnessed by D. F. Furse Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this I hereby swear or affirm that the information given above is true and correct.

7 day of March, 1947 Name Roy J. J. J.
Will Hale Taylor Notary Public Position Asst. Dist. Supt.
Representing Amerada Pet. Corp.
Company or Operator

My commission expires Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date MAR 10 1947

Roy J. J. J.
Oil & Gas Inspector
Title