Form 3160-5 November 1983) Formerly 9-331		UNITED STAT RTMEN OF THE		SUBMIT IN TRIPLICA (Other instructions "	Exp	ires August	10. 1004-013 31, 1985									
		REAU OF LAND MAN		, , , , , , , , , , , , , , , , , , , ,	LC-032		ND SERIAL NO.									
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)						6. IF INDIAN, ALLOTTEE OR TRIBE NAME										
1.					7. UNIT A	GRREMENT NAM	(B									
WELL A	AS VELL OTE	<u> </u>														
NAME OF OPERATOR						8. FARM OR LEASE NAME										
Exxon Corporation ADDRESS OF OFBRATOR P. O. Box 1600, Midland, TX 79702						Bowers A Federal 9. WBLL NO.										
									 LOCATION OF WI 	See also space 17 below.)						WILDCAT
At surface 1980' FSL and 660' FEL of Sec.						Hobbs Blinebry 11. EDC., T., R., M., OB ELK. AND SUBVEY OF ARRA Sec. 30, 18S, 38E										
									4. PERMIT NO.		15. ELEVATIONS (Sho	w whether DF, ST, C	2. etc.)		T OR PARIAR	
												3657' DF		Lea		NM
6.	Check	Appropriate Box To	Indicate Natur	e of Notice Report	or Other Data	<u>-</u>										
		TENTION TO :	1		TEORE THEORE											
TEST WATER SI	10 7-0FF	PULL OR ALTER CASING		WATER SHUT-OFF												
FRACTURE TREA	r	MULTIPLE COMPLETE		FRACTURE TREATMENT		REPAIRING WE	·									
SHOOT OR ACIDI	ZB	ABANDON®	x	SHOOTING OR ACIDIZING		ALTERING CAS										
REPAIR WELL		CHANGE PLANE		(Other)												
(Other)		OPERATIONS (Clearly state ectionally drilled, give sub		(Norm: Report res Completion or Rec	ults of multiple cupletion Report	completion on and Log form	₩ell									
 In: Set Set Set Bas Set bas Rut w/ Per est sal If Per 8. Est 7" 	stall and t plug 4100 Andres an csg. shoe. plug 2800 se of the s freepoint 100' plug forate 7" ablished s t. injection forate at ablish inj x 9 5/8" at	'-2550' w/ 20 sx alt. and cut 4 1/2" - 50' below and csg. at 1350' w/ et 100' plug 1400 is established - 280' w/ 4 shots. ection down 7" cs nnulus. Set sur	<pre>#. to cover t over old Qu to cover 9 csg. (TOC 2 50' above - 4 shots. 0'-1300' w/ squeeze w/ sg. Circul face plug w</pre>	op of Grayburg, een perforations 5/8" csg. shoe 200'). Cover st w/ 15 sx. If injection is 20 sx to cover 1C0 sx down 7" ate up 9 5/8 x 1	and ub not top of the csg.											
(This space for F	hat the foregoing		TLE Section		DATE	5-15	-86									
APPROVED BY _ CONDITIONS OF	APPROVAL, IF	ANT:	TLE		DATE											

*See Instructions on Reverse Side