

OWWO

COUNTY LEA FIELD Hobbs STATE NM MN 07471

OPR HUMBLE OIL & REFG. CO. MAP

1 Bowers "A" Federal

Sec 30, T-18-S, R-38-E CO-ORD

1980' FSL, 660' FEL of Sec

		CLASS		EL	
Re-Cmp 4-13-71		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
12 1/2" at 205' w/180 SX					
9 5/8" at 2750' w/620 SX					
7" at 3962' w/528 SX					
4 1/2" at 6000' w/275 SX					
LOGS EL GR RA IND HC A					
		TD 6000'			

(Blinebry) Perfs 5812-5922' NO NEW POTENTIAL.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 5922' TYPE WO

F.R.C. 5-13-71; Opr's Elev. 3657' DF
PD 5922' WO (Blinebry)
(Orig. comp 1-20-30 from OH 3962-4215',
OTD 4215'; OWWO & Re-Cmp 11-20-41 thru Perfs
3669-3726', OTD 4215', OPB 3900'; OWWO & Re-Cmp
4-30-69 thru (Blinebry) Perfs 5878-5922',
OTD 6000')
5-11-71 TD 6000'; COMPLETE
Perf (Blinebry) 5812-14', 5825-37', 5841-49'
w/1 SPF
Acid (5812-5922') 9000 gals (15%)
5-13-71 Ppd 90 BO + 10% wtr in 24 hrs (5812-5922')
COMPLETION REPORTED

OWDD

COUNTY	LEA	FIELD	Hobbs	STATE	NM	MN	07471
OPR	HUMBLE OIL & REFG. CO.						MAP
	1 Bowers "A" Federal						
	Sec 30, T-18-S, R-38-E						CO-ORD
	1980' FSL, 660' FEL of Sec.						
	Re-Spd 4-18-69		CLASS		EL		
	Re-Cmp 4-30-69		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING							
12 1/2" at 205' w/180 sx							
9 5/8" at 2750' w/620 sx							
7" at 3962' w/528 sx							
4 1/2" at 6000' w/275 sx							
LOGS EL GR RA IND HC A							
			TD 6000'				
IP (Blinebry) Perf 5878-5922' P 235 FOPD + 29 BW. Pot based on 24 hr test. GOR 112; Grav 36.							

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	6000'	TYPE	RT
DATE				

F.R. 4-15-69
PD 6000' RT (Blinebry)
(Orig. comp 11-20-41 from OH 3962-4215',
OTD 4215', OWWO & Re-Cmp thru Perfs 3669-3726')
4-21-69 Drlg. 4325' 1m
Sqzd (3669-3726') w/100 sx
4-28-69 TD 6000'; Prep run Logs
Deepened from 4215' to 6000'; Ran 4 1/2" casing
5-5-69 TD 6000'; Swbg
Perf @ 5878', 5888', 5900', 5908', 5918', 5922'
w/2 SPI
Acid (5878-5922') 2000 gals
Swbd 98 RC + 42 BLW in 10 hrs
5-12-69 TD 6000'; COMPLETE

LEA Hobbs NM Sec 30, T18S, R38E
HUMBLE OIL & REFG. CO. 1 Bowers "A" Federal Page #2

5-12-69 Continued
LOG TOPS: Glorieta 5365', Blinebry 5760'
5-15-69 COMPLETION REPORTED