
## (SUBMIT IN TRIPLICATE)

## **UNITED STATES**

## DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY



NOTICE OF INTENTION TO DRILL  NOTICE OF INTENTION TO CHANGE PLA  NOTICE OF INTENTION TO TEST WATER  NOTICE OF INTENTION TO SHOOT OR A  NOTICE OF INTENTION TO PULL OR ALT  NOTICE OF INTENTION TO ABANDON WI	NSSHUT-OFFR REPAIR WELLCIDIZE	SUBSEQUENT REPORT SUBSEQUENT REPORT SUBSEQUENT REPORT	OF WATER SHUT-OFF OF SHOOTING OR ACIDIZING OF ALTERING CASING	
NOTICE OF INTENTION TO TEST WATER NOTICE OF INTENTION TO RE-DRILL OR NOTICE OF INTENTION TO SHOOT OR A NOTICE OF INTENTION TO PULL OR ALT	SHUT-OFF REPAIR WELL CIDIZE	SUBSEQUENT REPORT	OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OF NOTICE OF INTENTION TO SHOOT OR AL	REPAIR WELL	SUBSEQUENT REPORT		
NOTICE OF INTENTION TO SHOOT OR A NOTICE OF INTENTION TO PULL OR ALT	CIDIZE		OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO PULL OR ALT			SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT	
		SUBSEQUENT REPORT		
NOTICE OF INTENTION TO ABANDON WI	TER CASING	SUPPLEMENTARY WEL	L HISTORY	
<u> </u>	ELL		·	
(INDICATE	ABOVE BY CHECK MARK NA	ATURE OF REPORT, NOTICE	E, OR OTHER DATA)	
		iloland, lexas	Saptember 15	, 19
Well No. 4-5 is locat	ted 330 ft. from	$1 \begin{Bmatrix} N \\ k \end{Bmatrix}$ line and $22$	<b>9ft.</b> from $\{E\}$ line of second	c
(% Sec. and Sec. No.)	18-5 3	18-7	au Pa	
Hobbs	(Twp.)	(Range)	(Meridian)	
(Field)		Subdivision)	(State or Territory)	
State names of and expected depths to of led well, wroke off two large. Laid down 25 joint a set at 3920'. Out a of bridge plug. Laid duiding, bet waker from le oil. Swabled well in averaged 15 barrels per	ing beac ama parts 7" casing the Casing at 20 lown drill pipe action Facker at 8 flowed 15 h	ured racker.  ured racker.  uses casing part  001 and recove  San 3705.50	Laid down 187 joints ad at 745.68'. Ran 5 red 198'. Ran 6-1/8 ' of 53" casing. Pi	3" Tidene bit t
I understand that this plan of work m	O11 & to ining			
Address ox 160	<b>U</b>			

. S CONSDUMENT BROWTHER CORRECT TO DARK D