

DISTRIBUTION: NEW MEXICO OCC

Mr. J. A. Grimes  
Mr. L. H. Shearer  
Mr. B. V. Kitley  
Mr. T. A. Steele  
Mr. T. O. Webb

(Form C-102)  
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET <del>LINE</del> <b>NEW</b> <del>string</del> <b>string csg</b>	<b>x</b>
NOTICE OF INTENTION TO SQUEEZE	<b>x</b>	NOTICE OF INTENTION TO ACIDIZE	<b>x</b>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<b>x</b>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

3/17/58  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State Sec. 30

THE OHIO OIL COMPANY

(Company or Operator)

Well No. 2 in N (Unit)

SE 1/4 SW 1/4 of Sec. 30, T. 18 S, R. 38 E, NMPM, Hobbs, Lea County, Pool

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

4230' TD; 4168' PBD: 7", 21# @ 3928' with 275 sx; 9-5/8", 40# @ 2750' with 550 sx; 12-1/2", 50# @ 294' with 275 sx.  
Move in pulling unit, pull 3" tbg & set bridge plug in 7" csg at approx. 3800' & test 7" csg above bridge plug. Perf 7" csg at approx. 2800' (above Bowers zone) with 4 holes & squeeze cement. Perf. 7" & 9-5/8" csg at approx. 1500' & circ. cement to surface on 7" x 9-5/8" annulus & 9-5/8" x 12 1/2" annulus. Drill out bridge plug & run 5" string csg to 4168' PBD. Selectively perf 5" csg in Grayburg and/or San Andres sections, treat with 500 gals mud acid & 2,000 gals reg if necessary & complete as Hobbs Pool oil well.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

THE OHIO OIL COMPANY  
ORIGINAL  
Company or Operator

By..... SIGNED BY: B. G. HOWARD

Position..... Asst. Supt.  
Send Communications regarding well to:

Name..... The Ohio Oil Company  
Address..... Box 2107, Hobbs, New Mexico