

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

January 8, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State Land Sec. 30

THE OHIO OIL COMPANY Well No. 4 in M  
(Company or Operator) (Unit)  
SW  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. 30, T. 18S, R. 38E, NMPM, Hobbs Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

4215' T.D., 3914' P.B.: 16" @ 260' with 225 sx, 9-5/8" @ 2750' with 500 sx, 7" @ 3946' with 350 sx. Cast iron bridge plug @ 3940' with 26' cement from 3940-3914', 7" csg perforated opposite Byers section from 3758' to 3850'.

Plug and abandon well as follows:

Load hole with mud, spot 300' cement plug from 3914' to 3600', leaving approx. 150' cement above Byers perfs. Cut 7" @ approx. 2750' & pull same. Set cast iron retainer in 9-5/8" csg @ approx. 2700' & squeeze 50 sx cement below retainer. Spot 100' cement plug on top of retainer approx. 2600'-2700'. Perf. 9-5/8" @ approx. 260' & circ. cement to surface on 9-5/8" x 16" annulus leaving approx. 260' cement plug in 9-5/8" csg. from surface to 260'. Install permanent well marker.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

THE OHIO OIL COMPANY

ORIGINAL Company or Operator

By..... SIGNED BY: A. G. HOWARD

Position..... Assistant Superintendent  
Send Communications regarding well to:

Name..... The Ohio Oil Company

Address..... Box 2107, Hobbs, New Mexico