Form C-161	NEW		IL CONSER	VATTON CC	TOOTAN		
	· · · · · · · · · · · · · · · · ·				SSION	f	
PLICA			Santa Fe, New	Mexico	11	In the second	
		NOTICE	OF INTENTI	ON TO DR		JUNT 1: 10 10	
otice must be	given to the O	il Conservation	Commission or	its proper ager	t and approva	JUNI 5 1947	
egins. If chang eturned to the	ges in the propo sender. Submit	sed plan are co t this notice in	nsidered advisal triplicate. One	le, a copy of the copy will be ret	his notice showing		
nstructions in ]	Rules and Regul	lations of the (	Commission.			BES OFFICE	
	·····		Hobbs, Ne	Mexico	June 13	5. 1947	
OIL CONSERV	ATION COMMI		PL	800		Date	
Santa Fe, New 1							
Gentlemen:							
You ar	e hereby notifie	d that it is our	intention to con	mmence the dril	lling of a well to	be known as	
raciilo W	estern 011	. corp.	H. D. Mc	Kinley	Well No. 7	inWV/4 XB/4	
				There			
	, T <b></b>	, <u>R. 994</u>	., N. M., P. M.,	BOWEIR	Field,L	County.	
<b>N</b>	· · · · · · · · · · · · · · · · · · ·	The well is	JOU feet	(S.) of the State	e SOTES line	e and 1650 feet	
		(Give loc directions.)	ation from sect	ion or other le	gal subdivision li	nes. Cross out wrong	
<b>I</b>		If state land	the oil and gas ]	ease is No	Assignm	nent No.	
		If patented land the owner isAddress					
		If government land the permittee is					
		The lessee is	Pact	fic West	rn Oil Cor	7.	
ABEA 640 /	ACRES	Address	Tuls	sa, Oklaho	)na		
LOCATE WELL	COBRECTLY	We propose to	drill well with	drilling equipme	nt as follows. Ro	tary tools fr	
top to tot	tal depth.			_			
The status of a	bond for this	well in confor				d Regulations of the	
Commission is a	s follows:			ne og or me (	Jeneral Rules an	a Regulations of the	
			g and to land or				
Size of	Size of Wei	sht Per Foot	New or	Dunth	Landed or	Becks	

Size of Hole	Size of Casing	Weight Per Foot	New or <del>Sec</del> ond Hand	Dopth	Landed or Cemented	Sacks Cement
11" 7"	8-5/8° 5-1/2"	<b>32#</b> 17#	X ew New	1500° 3150°	Cemented Cemented	400 150

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about **31.70** feet.

circulated back to surface. Halliburton process will be employed to	be
cement both strings of casing. JUN 15 1947	i

Approved 19	Sincerely yo	1175.
except as follows:	SKELLY	· ·
OIL CONSERVATION COMMISSION,	Position Send commu	District Supt.
By Coy yoularough.	Name	Skelly Oil Company
Title OIL & Gas Inspection	Address	Hobbs, New Mexico