

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name N. HOBBS (G/SA) UNIT
2. Name of Operator SHELL OIL COMPANY	8. Farm or Lease Name SECTION 31
3. Address of Operator P. O. BOX 991, HOUSTON, TX 77001	9. Well No. 211
4. Location of Well UNIT LETTER C, 440 FEET FROM THE NORTH LINE AND 2310 FEET FROM THE WEST LINE, SECTION 31 TOWNSHIP 18-S RANGE 38-E N.M.P.M.	10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3651' DF	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER SQUEEZED ZN I PERFS 4032'-4146'; DEEP-ENED TO OPEN ADDITIONAL PAY ZN III <input checked="" type="checkbox"/>			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-20-83: Cleaned out to 4210'. Dumped 400# 20-40 mesh sand to 4210'.
7-21-83: Tagged sand @ 4177'. Set Halliburton 5" EZ drill CIRC @ 3922'. Squeeze perfs 4032' to 4132' and 4146' w/50 sx Class "C" cmt + .3% Halad-4 and 2% CaCl2. WOC 24 hrs.
7-25-83: Tagged cmt @ 3912'. Drilled CIRC @ 3922'.
7-26-83: Drilled reamer of CIRC and cmt to 4182'. Pressure tested squeezed perfs 4032' - 4132' and 4146' to 500#, held OK. Tagged btm @ 4210'. Drilled shoe @ 4210' and new hole to 4238'.
7-27-83: Drilled new hole 4238' to 4300'.
7-28-83: Acidized open hole 4210' to 4300' (90') w/1800 gals 15% HCl-NEA acid.
7-29-83: Perf'd 4186' to 4196' (6 holes). Acidized perfs 4186' to 4196' w/600 gals 15% HCl-NEA. Installed production equipment and returned well to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie Carter Jr. A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE AUGUST 5, 1983

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE AUG 8 1983