

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-07506
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. 014959
7. Lease Name or Unit Agreement Name Clara Fowler
8. Well No. 4
9. Pool name or Wildcat Bowers Seven Rivers
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3650' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Lewis B. Burleson, Inc.
3. Address of Operator P.O. Box 2479 Midland, Texas 79702	4. Well Location Unit Letter F : 1650 Feet From The North Line and 2310 Feet From The West Line Section 31 Township 18-S Range 38-E NMPM Lea County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. MIRU Install BOP
2. Set 50 sacks cement plug at TD 3278 to cover casing shoe at 3170'. Tag plug
3. Set 25 sack cement plug at 2700-2600. Tag if hole not static
4. Set 25 sack cement plug at 1600-1500'.
5. Set 25 sack cement plug at 840'-740'.
6. Perf 7" casing at 490' TOC at 495'. Cement with sufficient volume to fill to surface.
7. Cut off and install marker.

THE COMPLETION OF THE ABOVE
HOURS EACH DAY OF THE
PLUGGING OPERATIONS IS TO
BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steven L. Burleson TITLE Vice-President DATE 1/18/2002
TYPE OR PRINT NAME Steven L. Burleson TELEPHONE NO. 915/ 683-4747

(This space for State Use)

APPROVED BY PAUL F. KAUF TITLE PETROLEUM ENGINEER DATE FEB 11 2002