

N.

NEW MEXICO STATE LAND OFFICE
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days
after completion of well. Indicate questionable data by fol-
lowing it with (?). Submit in duplicate.AREA 640 ACRES
LOCATE WELL CORRECTLY

Company Amerasia Petroleum Corp. Address Box 1348, Fort Worth, Texas.
Send correspondence to do Address Hobbs, N.M.
St. to A Well No. 1 in S. 1/4 NE 1/4 of Sec. 32 T. 18s
R. 38s, N. M. P. M., Hobbs Oil Field Lea County.
If State land the oil and gas lease is No. A-1469 Assignment No. Taken Direct
If patented land the owner is _____, Address _____
The lessee is _____, Address _____
If not state or patented land, give status _____
Drilling commenced May 12, 1930 19 ____ Drilling was completed August 7, 1930 19 ____
Name of drilling contractor Noble Drilling Co. Address Tulsa, Oklahoma
Elevation above sea level at top of casing 3643 feet.
The information given is to be kept confidential until _____ 19 ____

OIL SANDS OR ZONES

No. 1, from <u>2917</u> to <u>2922</u>	No. 4, from <u>3129</u> to <u>3138</u>
No. 2, from <u>2925</u> to <u>2927</u>	No. 5, from <u>3862</u> to <u>3872</u>
No. 3, from <u>3020</u> to <u>3030</u>	No. 6, from <u>3966</u> to <u>4160</u>

IMPORTANT WATER SANDS

No. 1, from <u>16</u> to <u>112</u>	No. 3, from _____ to _____
No. 2, from <u>121</u> to <u>190</u>	No. 4, from _____ to _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT AND PULLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>12 1/2</u>	<u>50 1/2</u>	<u>8</u>	<u>eld</u>	<u>207'</u>	<u>TP</u>				
<u>9 5/8</u>	<u>40 1/2</u>	<u>8</u>	<u>Sals</u>	<u>2739</u>	<u>Baker</u>				
<u>7"OD</u>	<u>24 1/2</u>	<u>10</u>	<u>"</u>	<u>3938</u>	<u>"</u>				

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>12 1/2</u>	<u>207</u>	<u>200</u>	<u>Halliburton</u>		
<u>9 5/8</u>	<u>2739</u>	<u>425</u>	<u>"</u>		
<u>7"OD</u>	<u>3938</u>	<u>350</u>	<u>"</u>		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from 207 feet to 4160 feet, and from _____ feet to _____ feet
Cable tools were used from Surface feet to 207 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing August 9, 1930 19 ____
10
The production of the first 24 hours was 7583 barrels of fluid of which 66 % was oil; _____ %
emulsion; 27 % water; and 7 % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____ Note : At end of test water was 7% and
sediment 7%.

EMPLOYEES

G. D. Morris _____, Driller _____, Driller
T. S. Offutt _____, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work
done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14 Name F. A. Mackey
day of July, 19 30 Position Production Foreman
F. A. Mackey Representing Amerasia Pet. Corp.
Notary Public. Company or Operator
My commission expires June 1, 1931

DUPLICATE
7-17-33
L. B. Hunter

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	16	16	Cellar
16	112	96	Sand
112	121	9	Hard Lime
121	190	69	Sand
190	415	225	Red Beds
415	1230	815	Shale
1230	1300	70	Sand & Lime
1300	1387	87	Shale
1387	1436	49	Anhydrite
1436	1455	19	Sand & Shale
1455	1495	40	Gyp
1495	1520	25	Anhydrite
1520	1569	49	Anhydrite & Lime
1569	1590	21	Anhydrite & Gyp
1590	1608	18	Anhydrite & Shale
1608	2510	902	Anhydrite & Salt
2510	2760	250	Anhydrite
2760	2857	97	Anhydrite & Lime
2857	2872	15	Anhydrite
2872	2892	20	Lime & Anhydrite
2892	2917	25	Anhydrite
2917	2922	5	Sand oil show
2922	2995	73	Anhydrite
2995	3009	14	Anhydrite & Shale
3009	3020	11	Anhydrite
3020	3030	10	Sand
3030	3084	4	Anhydrite
3084	3085	1	Anhydrite & Sand
3085	3038	3	Sand
3038	3084	46	Anhydrite & Shale
3084	3090	6	Oil Sand
3090	3102	12	Anhydrite
3102	3105	3	Lime & Sand
3105	3108	3	Anhydrite
3108	3128	20	Lime & Anhydrite
3128	3129	1	Anhydrite
3129	3138	9	Gas Sand
3138	3196	58	Anhydrite
3196	3223	27	Shale & Anhydrite
3223	3278	55	Anhydrite
3278	3285	7	Anhydrite & Lime
3285	3367	82	Anhydrite & Shale
3367	3392	25	Anhydrite & Sand
3392	3400	8	Anhydrite
3400	3403	3	Blue Shale
3403	3469	66	Anhydrite
3469	3494	25	Anhydrite & Lime
3494	3500	6	Anhydrite & Sand
3500	3529	29	Anhydrite & Lime
3529	3546	17	Anhydrite & Sand
3546	3559	13	Anhydrite
3559	3608	49	Anhydrite & Lime
3608	3610	2	Brown Lime
3610	3629	19	Lime & Anhydrite
3629	3641	13	Anhydrite
3641	3680	39	Anhydrite & Lime
3680	3700	20	Hard Lime
3700	3707	7	Sandy Lime
3707	3730	23	Lime & Anhydrite
3730	3734	4	Lime
3734	3741	7	Black Lime
3741	3749	8	Anhydrite
3749	3780	31	Black Lime
3780	3787	7	Anhydrite & Lime
3787	3800	13	Black Lime
3800	3827	27	Brown Lime
3827	3893	66	Lime
3893	3900	7	Brown Lime
3900	3920	20	Grey Lime
3920	3933	13	Grey Sandy Lime
3933	3951	18	Gray Lime
3951	3964	13	Gray Sandy Lime
3964	3992	28	Crystalline Lime
3992	3995	3	Brown Lime
3995	4019	24	Gray Lime
4019	4023	4	Lime Shells
4023	4037	14	Lime & Streaks of Sand
4037	4060	123	Lime