

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Plug back and perforate casing in big gas zone XX

Hobbs, New Mexico
Place

September 2, 1940
Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corp-Gypsy Prodn. Division West Grimes Well No. 4 in the
Company or Operator Lease

NE NE NW of Sec. 32, T. 18S, R. 36E, N. M. P. M.,
Hobbs Lea County

The dates of this work were as follows: Cemented Aug 21, 1940. Casing perforated Aug 26, 1940

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on June 21, 1940
and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Aug 21, 1940. Original T.D. 4153', a canvas packer set at 4035' on 3" tubing. Out tubing off at 4000', set Baker Cement retainer at 3909' and squeezed 70 sac 4% Aquagel cement below and placed 5 sac 4% Aquagel cement on top of retainer, Present T.D. 3905'. After cement set, swabbed dry and tested dry for 1 hour.

Aug 26, 1940: Perforated 7" casing as follows:

Depth	No. Holes	Approx. Intervals	Depth	No. Holes	Approx. Intervals
3700-3685	4	5'	3670-3660	43	3" (Main gas)
3684-3675	11	1'	3659-3646	28	6"
3674-3670	10	6"	3645-3630	4	5'

After shots tested 23,750,000 cu. ft. gas. Shut in pressure 1625#.

Witnessed by

C. C. Cummings

Gulf Oil Corporation

Company

District Superintendent

Title

Subscribed and sworn to before me this
2nd day of September, 1940

J. W. Egan

Notary Public

My Commission expires February 25, 1942.

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name *Ray Yarbrough*

Position District Superintendent

Representing Gulf Oil Corp-Gypsy Prodn. Div.
Company or Operator

Address Hobbs, New Mexico.

Ray Yarbrough
Name
OIL & GAS INSPECTOR
Title