

NE MEXICO OIL CONSERVATION CO. COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commissioner or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

HOBBS OFFICE

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL			
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF INTENTION TO PLUG WELL &	

Perforate csg to produce big gas XX

Hobbs, New Mex.

June 21, 1940

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the Gulf Oil Corporation -  
Gypsy Prodn. Division West Grimes Well No. 4 in NE NE NW  
 Company or Operator Lease  
 of Sec. 32, T. 18S, R. 36E, N. M. P. M., Hobbs Field,  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Authority is requested to plug with cement from total depth to casing seat and perforate casing between 3630' and 3700', or into Byars "big gas" zone. This gas is to be used to gas-lift other wells in Hobbs Pool (Immediate need at North Grimes Nos. 3 and 4 in Sec. 21-18S-36E).

This well now has a canvas packer set at 4035' and one unsuccessful attempt was made in 1934 to remove it. Should it be impossible to remove the packer now the tubing will be cut off immediately above the packer and a Baker Cement Retainer set near the bottom of the casing. Heavy Fiber-Aquagel mud will then be pumped through the cement retainer to plug the lower producing section. Then 30' of cement will be placed on top of the retainer to insure successful shut off. With the lower section properly plugged the casing will then be perforated as described above.

Approved \_\_\_\_\_, 19\_\_\_\_  
 except as follows:

Gulf Oil Corporation - Gypsy Prodn. Div.  
 Company or Operator

By C. C. CummingsPosition District Superintendent

Send communications regarding well to

Name C. C. CummingsAddress Hobbs, New Mexico.

OIL CONSERVATION COMMISSION,

By Roy Yarkrough

OIL &amp; GAS INSPECTOR

Title \_\_\_\_\_