

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

1954 MAR 26 PM 2:04

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|--|--|--|---|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

Repair 7" Casing
Leak XX

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 26, 1954
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the West Grimes

Gulf Oil Corporation
(Company or Operator)

Well No. 8 in E (Unit)

SW 1/4 Sec. 32, T. 18-S, R. 38-E, NMPM, Hobbs Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to repair 7" OD casing leak as follows:

1. Set bridge plug in base of 7" casing.
2. Run retrievable cementer and locate leak.
3. Perforate 7" casing at approximately 2100' (This will be approximately 100' above the calculated top of cement behind the 7" casing.)
4. Cement 7" - 9-5/8" annulus from 2100' to surface.
5. Connect to 9-5/8" - 15-1/2" bradenhead and fill the 9-5/8" - 15-1/2" annulus with cement.
6. WOC
7. Drill out and pressure test 7" casing with 1000 psi for 30 minutes.
8. If pressure holds, drill out bridge plug and return well to production.

Approved....., 19.....
Except as follows:

Gulf Oil Corporation
Company or Operator

By

Position Area Prod. Supt.
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By

Name Gulf Oil Corp.

Title

Address Box 2167, Hobbs, N.M.