

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report of abandonment of unfinished hole and change in location	x

April 6, 1948

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Gulf Oil Corporation W. Grimes Well No. 14 in the _____
 _____ Company or Operator _____ Lease _____
NE SW SW of Sec. 32, T. 18S, R. 38E, N. M. P. M.,
Bowers Field, _____ Lea _____ County.

The dates of this work were as follows: See Below

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on April 6, 1948
 and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Because of blow-out and lost circulation difficulties, it was necessary to abandon and plug the hole located 660' from West Line and 660' from South Line of Section 32-18S-38E, which had been drilled to a total depth of 2600', and spud a new hole located 990' from South Line and 990' from West Line of Section 32-18S-38E. First hole was plugged by injecting a total of 320 sacks of cement through drill pipe from a depth of 228'. This filled the hole to the surface and it was then capped with 4 sacks of cement and abandoned on April 1, 1948. New hole was spudded on April 2, 1948.

Witnessed by A. Clarkson Gulf Oil Corporation Foreman
 Name Company Title
 Subscribed and sworn before me this _____
6th day of April 1948 Name E. J. Gallagher
A. W. Langham Position District Sup't.
 Notary Public Representing Gulf Oil Corporation
 Company or Operator
 My commission expires 10-24-49 Address Box 1667, Hobbs, New Mexico

Remarks:

Name

Title