STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

ים טבו וויו נוווו נוווו ווווו		
MO. OF COPIES ACCEIVED	1	
DISTRIBUTION		
SANTA FE		
FILE		<u> </u>
U.S.G.3.		
LAND OFFICE		L
OPERATOR		١

SHELL OIL COMPANY

P. O. BOX 991, HOUSTON, TX 77001

WELL X 2. Name of Operator

3. Address of Operator

4. Location of Well

PERFORM REMEDIAL WORK

DIVISION CO 87501

AGY AND MINCHARD DEL MILLION	OIL CONSERVATION			
NO. OF COPIES RECEIVED				
DISTRIBUTION	P. O. BOX 2088			
SANTA FE	SANTA FE, NEW MEXIC			
FILE				
U.S.G.3.				
LAND OFFICE				

32

NOTICE OF INTENTION TO:

SUNDRY NOTICES AND REPORTS ON WELLS

[DO NOT USE THIS FORM FOR PHOPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.

[DO NOT USE TAPPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

3634' GR

N	!	Form C-103 . Revised 10-1-78
	Sa. Indicate Type of State XX 5. State Oil & Gas L	F.00-
ERVOIR.		
	7. Unit Agreement N N. HOBBS (1 8. Farm or Lease No.	G/SA) UNIT
	SECTION 32 9. Well No. 441	
FEET FROM	10. Field and Pool, HOBBS (G/S	
E NMPM.		
	12. County LEA	
Report or Oth	her Data T REPORT OF:	
opns.		G CASING

WATER SHUT-OFF 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SOUTH LINE AND 660

18-S

15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report

38-E

- Set cement retainer @ 3980'+. Squeeze perforations @ 4060' to 4087' w/50 sx Class "C" cement containing 2% CaCl2. WOC 24 hrs.
- Drill out cement and cement retainer to 4090'+. Pressure test squeeze to 500 psi.
- Install production equipment and return well to production.

•		
18. I hereby cartify that the information above is true and complet	e to the best of my knowledge and belief.	
// / //	SUPERVISOR REG. & PERMITTING	MAY 17, 1983
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		.MAY 23 1983
CONDITIONS OF APPROVAL, IF ANY:	AIAFE	•

MAY 20 1983

HOBBS OFFICE

į.