

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	372	372	Caliche, sand, red bed
372	924	552	Red bed
924	1130	205	Red bed and shells
1130	1230	100	Red bed and shale
1230	1550	320	Red bed and sand
1550	1690	140	Sand and anhydrite
1690	2550	860	Anhydrite and salt
2550	2655	105	Anhydrite and gypson
2655	2920	265	Anhydrite and shale
2920	3115	195	Anhydrite and shells
3115	3140	25	Anhydrite and lime
3140	3210	70	Lime and shale
<p>Well was drilled to total depth of 3210 feet, lime. Well was not shot. Well was not acidized. Completed for initial potential of 72 barrels oil, no water in 24 hours, based on 24 hour test, flowing through 16/64" choke on 2" tubing, with 57 MCF gas, GOR 792, C.P. 700#, T.P. 25#. Pay: Bowers from 3161 to 3170. Pipe line connections: Humble Pipe Line Company Derrick floor 10' above ground. Date total depth reached: 10-13-48 Date completion test: 10-20-48</p>			
<p>NT-DF Hobbs, N.M. 11-12-48</p>			
<p>Copies to: U.S.G.S. Orig/2 HBH/2 HM KSB File</p>			
<p>RECEIVED</p>			
<p>APR 14 1971</p>			
<p>OIL CONSERVATION COMM. HOBBS, N. M.</p>			