

Rec'd and Fwd.
T. A. Stanchitt
State Oil & Gas Inspector

Form SG 108

N.

NEW MEXICO STATE LAND OFFICE

SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days after completion of well. Indicate questionable data by following it with (Tulsa, Oklahoma) Box 661

AREA 640 ACRES
LOCATE WELL CORRECTLY

Company **Gypsy Oil Company** Address **Hobbs, New Mexico - Drawer K**
East Grimes (2) **SE/4 - NE/4** 38 183
Send correspondence to 383 Well No. **Hobbs** in of Sec. **Lea**, T.
R. N. M. P. M. Oil Field County.
If State land the oil and gas lease is No. **W.D. Grimes** Assignment No. **Lubbock, Texas**
If patented land the owner is **Gypsy Oil Company** Address **Tulsa, Oklahoma**
The lessee is Address
If not state or patented land, give status **September 18, 32** **October 28, 32**
Drilling commenced **Loffland Bros. Company** Drilling was completed **Tulsa, Oklahoma**
Name of drilling contractor **3642** Address
Elevation above sea level at top of casing **Not confidential**
The information given is to be kept confidential until 19

Anhydrite **Top** **SANDS OR ZONES** **Swers Sand** **3168**
No. 1, from **Salt** to **1725** No. 4, from **Terry Lime** to **3988**
No. 2, from **Brown Lime** to **2810** No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from to No. 3, from to
No. 2, from to No. 4, from to

CASING RECORD

DATE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF	CUT & PULLED FROM	PERFORATED		PURPOSE
			NAVL.				FROM	TO	
13-3/8	36	8	"	2761	Baker				
9-5/8	24	10	"	3989	Baker				
6-5/8									

MUDDING AND CEMENTING RECORD

DATE	WHEN SET	NO. SACKS OF CEMENT	EXPIRATION	MUD GRAVITY	AMOUNT OF MUD USED
13-3/8	2761	800	Halliburton		100 ton
9-5/8	3989	280	Halliburton		Water
6-5/8					

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 4,651.9 100 182
The production of the first 24 hours was 35.4 barrels of fluid or 35.4 % was oil; %
emulsion; % water; and 6,215,000 sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours 1500 Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

A.H. Holder

EMPLOYES

J.T. House

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9th Name **District Superintendent**
day of **November**, 19 **32** Position **GYPSY OIL COMPANY**
Mary Frances Beal Representing
Notary Public. Company or Operator.
My commission expires **June 10 34**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	215	215	Surface
215	241	26	Red Bed
241	245	4	Sand Rock
245	457	212	Red Bed
457	1115	658	Red Bed and Anhydrite
1115	1227	112	Broken Lime
1227	1313	86	Broken Anhydrite
1313	1384	71	Shale and Shells
1384	1394	10	Broken Sand
1394	1464	70	Broken Lime
1464	1543	79	Red Bed and Broken Lime
1543	1575	32	Broken Lime and Sand
1575	1582	7	Anhydrite
1582	1606	24	Broken Shale.
1606	1745	139	Anhydrite
1745	1785	40	Shale and Red Bed
1785	1800	15	Anhydrite
1800	2540	740	Salt
2540	2680	140	Lime
2680	2818	138	Broken Anhydrite
2818	2838	20	Lime
2838	3187	349	Broken Anhydrite
3187	3212	25	Oil Sand
3212	3308	96	Broken Anhydrite
3308	3340	32	Lime and Shells
3340	3688	358	Broken Anhydrite
3688	3705	7	Broken Sand
3705	3896	191	Anhydrite
3896	3959	63	Lime and Anhydrite
3959	3963	4	Lime
3963	3989	26	Broken Lime and Sand
3989	4005	16	Sandy Lime
4005	4163	158	Lime (Terry)

REMARKS: Total depth 4163, top lime 3968.
First gas at 2820'. No estimate of same, but
very small volume. Show oil at 3168' with
increase in gas and now estimated at 1 mi.

Mudded hole at 3680'.

First oil show in Terry lime at 4005'.