

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Repr. Csg. Leak</b>	<b>X</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)March 15, 1954  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the W. D. Grimes (East)Gulf Oil Corp.

(Company or Operator)

Well No. 3 in B  
(Unit)NW  $\frac{1}{4}$  NE  $\frac{1}{4}$  of Sec. 33, T. 18-S, R. 38-E, NMPM, Hobbs Pool

(40-acre Subdivision)

Lea County.FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to repair 5-1/2" and 7" casing leaks using the following procedure:

1. Set bridge plug in base of 5-1/2" casing.
2. Locate 5-1/2" casing leak using a retrievable cementer.
3. Run cement retainer and set above leak and attempt to circulate water out 5-1/2" and 7" annulus. Close 5-1/2" - 7" casing annulus and attempt to circulate out 7" - 9-5/8" annulus.
4. If circulation is obtained, pump cement thru 5-1/2" casing leak until cement circulates out 5-1/2" - 7" annulus then close gate and circulate cement out 7" - 9-5/8" annulus.
5. Wait on cement.
6. Drill out cement and pressure test 5-1/2" casing.
7. Drill out bridge plug and return well to production.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy J. G. Stanley

Title \_\_\_\_\_

Gulf Oil Corp.  
Company or OperatorPosition Area Prod. Supt.  
Send Communications regarding well to:Name Gulf Oil Corp.Address Box 2167, Hobbs, New Mexico