NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL		
		Hobbs, New Hexico July 5. 19
		Place July 5, 19
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.		
Gentlemen:		
Following is a notice of intention to do certain work	as de	scribed below at the
Didivilio VII & Gas Company Susta 1	IAII	ract 10 Wall No 237
of Sec. 33 , T. 18-5 , R. 38-E	, N	. M. P. M., cowers
•	ND 0 7	OGDD DY 122
FOLLOW INSTRUMENTATION OF F	KOP	OSED PLAN OF WORK
TODDOW INSTRUCTIONS IN THE RUI	ES A	ND RECHLATIONS OF THE COMME
52" casing set at 3160', and cemented At this time it is planned to test pip pressure and holding for 30 minutes.	ES A 1rs v with 0e ar	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 in and after shut off by applying 1000 in a shut of the sh
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and cemented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PST according to the state of 100 PST according to 100 PST	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and comented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occurred be carried out. In the event the	ES A lrs with le ar lefor	ND REGULATIONS OF THE COMMISSION Till have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug.
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and cemented At this time it is planned to test pip pressure and holding for 30 minutes, is pressure drop in excess of 100 PSI occavill be carried out. In the event the drilling will then be resumed.	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 le and after drilling cement plug. on either test, proper remedial measure tests satisfactorily meet require
on July 7, 1949, at 12:01 a.m., 48 hor 52" casing set at 3160', and cemented At this time it is planned to test pip pressure and holding for 30 minutes, is pressure drop in excess of 100 PSI occavill be carried out. In the event the drilling will then be resumed.	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string divater shut off by applying 1000 He and after drilling cement plug. on either test, proper remedial measure tests satisfactorily meet required tests.
pproved coept, as follows:	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 He and after drilling cement plug, on either test, proper remedial measure tests satisfactorily meet require
pproved coept, as follows:	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string divater shut off by applying 1000 He and after drilling cement plug. on either test, proper remedial measure tests satisfactorily meet required tests.
pproved coept, as follows:	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3157 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug. On either test, proper remedial measure tests satisfactorily meet required tests satisfactorily meet required tests. Stanolina Oil and Gas Company Company or Operator By
pproved coept, as follows:	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151. 700 sacks to be used as oil string a water shut off by applying 1000 is e and after drilling cement plug. on either test, proper remedial measure tests satisfactorily meet required tests satisfactorily meet required tests. Stanolina Oil and Gas Company Company or Operator By
pproved copy as follows: [1.10] a.m., 48 hou 52" casing set at 3160', and cemented At this time it is planned to test pip pressure and holding for 30 minutes, to pressure drop in excess of 100 PSI occ will be carried out. In the event the drilling will then be resumed. pproved copy as follows: [1.10]	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3151 700 sacks to be used as oil string a water shut off by applying 1000 re and after drilling cement plug. On either test, proper remedial measure tests satisfactorily meet require tests satisfactorily meet require Company or Operator By
casing set at 3160°, and cemented this time it is planned to test piperessure and holding for 30 minutes, to pressure drop in excess of 100 PSI occill be carried out. In the event the brilling will then be resumed. Oproved cept as follows: OIL CONSERVATION COMMISSION,	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 3157. 700 sacks to be used as oil string a water shut off by applying 1000 is and after drilling cement plug. On either test, proper remedial measure tests satisfactorily meet required tests satisfactorily meet required by the company of the
casing set at 3160', and cemented this time it is planned to test piperessure and holding for 30 minutes, to pressure drop in excess of 100 PSI occill be carried out. In the event the brilling will then be resumed. Oproved cept, as follows: Out Conservation Commission,	ES A lrs v with pe ar pefor curs abo	ND REGULATIONS OF THE COMMISSION will have elapsed since running 31: 700 sacks to be used as oil string water shut off by applying 1000 e and after drilling cement plug. On either test, proper remedial meave tests satisfactorily meet required tests satisfactorily meet required by Company or Operator By Company or Operator Position Production Foreman Send communications regarding well Name Harold & Herndon