


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



HOBBSS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	X
REPORT ON RESULT OF PLUGGING OF WELL		Run and Cement Liner	X

Hobbs, New Mexico

Place

12-19-45

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Oil Company, Inc.

Company or Operator

State B

Lease

Well No. 2

in the

NW/4 of Sec. 33, T. 18 S, R. 38 E, N. M. P. M.,

Hobbs

Field,

Lea

County.

The dates of this work were as follows: 11-29 to 12-18-45

Notice of intention to do the work was (was not) submitted on Form C-102 on 11-28-1945

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Deepened hole from 4220 to 4227. Ran 5 1/2-inch flush joint liner from 3887 to 4226 and cemented with 82 sacks cement. Drilled cement out to 4225. Perforated liner from 4122 to 4222 with 4 shots per foot. Treated perforations with 500 gallons acid and set packer at 3814. Swabbed well in. On official gas-oil ratio test flowed 92 barrels oil out 3/10 per cent B.S. in 24 hours through 9/64-inch choke. Tubing pressure 565 pounds. Gas-oil ratio 1280.

Witnessed by W. R. Bollinger Name Shell Oil Company, Inc. Dist. Engineer
Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

19th day of December, 1945

Name *W. R. Bollinger*

Position District Superintendent

Notary Public

Representing Shell Oil Company, Inc.
Company or Operator

My commission expires

Address Box 1457, Hobbs, New Mexico

Remarks: APPROVED

Date

JAN 2 1945

Ray Yachrow
Oil & Gas Inspector
Title

