NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

1		Notice by Checking 1	Below	
Notice of Intention to Change Plans	Notice of Intention Temporarily Abani		Notice of Intention to Drill Deeper	
Notice of Intention o Plug Well	Notice of Intention to Plug Back	N	Notice of Intention to Set Liner	
Notice of Intention to Squeeze	Notice of Intention To Acidize	И	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	Notice of Intentic (Other) Reduc		Notice of Intention (Other)	
OIL CONSERVATION COMMISSI SANTA FE, NEW MEXICO	ION lis bbs	, New Mexico		er 7, 19 58
Gentlemen:		(Place)	(Date)	
Following is a Notice of Intentio	on to do certain work as descri	ibed below at the	Pan American Petrole	um Corporati
В. Н.	furner Tract 2		Well No.	L
(Company or 6	Operator) 34, T. 18-S	, R. 38-E NMP	., Hobbs	(Unit)
Les				
	high GCR we propose r with sand from 422	-	: set retri evable reta i	ner at
Fill 5-1/2" lines	r with sand from 422	22' to 4180',		
Fill 5-1/2" lines approximately 3900"	r with sand from 422	22' to 4180', a	set retrievable retai	low set
Fill 5-1/2" lines approximately 3900° cement. Drill plug	r with sand from 422 and squeeze perform and clean out sand	22' to 4180', a	set retrievable retai	low set
Fill 5-1/2" lines approximately 3900"	r with sand from 422 and squeeze perform and clean out sand	22' to 4180', a	set retrievable retai	low set
Fill 5-1/2" lines approximately 3900° cement. Drill plug	r with sand from 422 and squeeze perform and clean out sand	22' to 4180', a	set retrievable retai	low set
Fill 5-1/2" lines approximately 3900' coment. Drill plug return well to produ	r with sand from 422 and squeeze perform and clean out sand	22' to 4180', a	set retrievable retai	low set
Fill 5-1/2" lines approximately 3900' cement. Drill plug return well to produ	r with sand from 422 and squeeze perform and clean out sand action.	22' to 4180', ation above 414 to 4222'. Set	set retrievable retai	est, and
Fill 5-1/2" lines approximately 3900' cement. Drill plug return well to produce the produce of t	r with sand from 422 and squeeze perform and clean out sand action.	22' to 4180', ation above 414 to 4222'. Set	rican Petroleum Corpo	est, and
approximately 3900° coment. Drill plug return well to produce the	and squeeze performand clean out sand action.	Pan Amer By Angles Position Field	rican Petroleum Corpo	est, and
approximately 3900' coment. Drill plug return well to produce Approved	and squeeze performand clean out sand action.	Pan Amer By Angles Position Field	ricen Petrolsum Corpo Company or Operator Communications regarding we	est, and