

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**SANTA FE, NEW MEXICO**

**MISCELLANEOUS NOTICES**

**RECEIVED**  
**FEB 23 1948**  
**RECEIVED**  
**HOBBS OFFICE**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

February 17, 1948

Place

Date

OIL CONSERVATION COMMISSION,  
 Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_  
 Stanolind Oil and Gas Company B. H. Turner Tr. 1 Well No. 8 in NW/4 of NW/4  
 Company or Operator Lease  
 of Sec. 34, T. 18-S, R. 38-E, N. M. P. M., Hobbs Field.  
 Lea County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**

**FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION**

Present total depth of this well is 4199' and 7" casing is set at 3976'. In order to eliminate hazards of corrosion we propose to pull the packer, set at 4120, and deepen the well approximately 27'. The 7" casing will be tested for leaks, perforated at the lowest possible point, and cement circulated behind the 7". a 5" liner will be cemented with approximately 100 sacks from TD to about 50' inside the bottom of the 7" casing. The remainder of the new 5" oil string will be connected to the top of the 5" liner and a packer will be set above this connection to pack off the annulus between the 5" and 7". A radioactive survey will be made and the 5" liner perforated opposite the pay. The well will be acidized as needed and sweet oil will be placed in the annulus between the 5" and 7" casing.

Approved \_\_\_\_\_, 19\_\_\_\_  
 except as follows:

FEB 23 1948

Stanolind Oil and Gas Company  
 Company or Operator

By \_\_\_\_\_

Position Field Supt.

Send communications regarding well to

Name R. L. Hendrickson

Address Box F

Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By Ray Parkhurst  
 Title OIL & GAS INSPECTOR