

NEW MEXICO STATE LAND OFFICE
OFFICE OF THE STATE GEOLOGIST
SANTA FE, NEW MEXICO

MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas Inspector if possible.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF SHOOTING WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF ABANDONMENT OF WELL		REPORT ON ACID TREATMENT	X

Mr. E. H. Wells State Geologist, Hobbs, New Mexico August 31, 1934
 Santa Fe, N. Mex. PLACE DATE

Following is a report on the work done and the results obtained under the heading noted above at the Stanolind Oil and Gas Company Turner Well No. 8 in the
 COMPANY OR OPERATOR LEASE
NW 1/4 of Sec. 24, T. 18 S, R. 38 E, N. M. P. M.,
Hobbs Oil Field, Lea County.
 The dates of this work were as follows: Acid treatment on August 24, 1934
 Notice of intention to do the work was (~~recorded~~) submitted on Form SG 105 on
August 20, 1934, and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was treated with 2,000 gallons 55% commercial Hydrochloric acid solution on August 24th. The well was shut in and left shut in for twenty four hours, until August 26th, when it was swabbed in. The well was then shut in until the official proration test which was made on August 30th. After acid treatment the potential is 7355 barrels of oil with 8,509,000 cubic feet of gas. Open flow test through tubing and casing on proration test was 7355 barrels.

DUPLICATE

Subscribed and sworn to before me this

31st day of August, 1934.

[Signature]
 NOTARY PUBLIC.

My commission expires October 17th, 1934.

I hereby swear or affirm that the information given above is true and correct.

Name J. H. Gibbins
 Position Production Foreman
 Representing Stanolind Oil and Gas Company
 COMPANY OR OPERATOR.
 Address Hobbs, New Mexico

Remarks:

SEP 7 - 1934

APPROVED AS O. K.

[Signature]

NAME

TITLE

REPORT ON THE PROGRESS OF THE
RESEARCH AND THE RESULTS OF THE
EXPERIMENTS

RESULTS AND CONCLUSIONS

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.

The results of the experiments carried out in the laboratory of the Department of Physics, University of Cambridge, during the period from 1948 to 1954, are presented in this report. The experiments were designed to investigate the properties of the new material, and to determine its suitability for use in the construction of a new type of electronic device. The results show that the material has a number of properties which are very different from those of the materials which it is intended to replace. In particular, it has a much higher resistance to corrosion, and it is much more stable under the conditions of use to which it is intended to be subjected. It is therefore concluded that the material is well suited for use in the construction of a new type of electronic device, and that it is likely to be of great value in the development of new types of electronic equipment.