

NEW MEXICO STATE LAND OFFICE  
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST  
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Wink, Texas

N. Mex., July 18, 1932

Mr. H. C. Wells

State Geologist,  
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in  
Well No. 1 in NW/4 of Sec. 34, T. 18S, R. 88E,  
N. M. P. M., Hobbs Oil Field Los County,  
on July 18, 19 32 12-1/2"-80 lb. casing was landed AAAAA {  
formation at a depth of 222' feet on July 18, 19 32 {  
804 sacks of El Toro Portland cement were used.

The method used in placing the cement was as follows:

Cemented through 12-1/2" with Halliburton Process,

Fluid level will be bailed to a depth of 222' feet and left undisturbed for at least  
12 hours before your inspection.

Adjacent property owners have been notified as follows: The Mid-West is being notified  
verbally.

Additional information:

Approved July 18 19 32 Sincerely yours,

Except as follows:

Skelly Oil Company

Company or Operator.

By J. G. GreedenPosition Division Superintendent

Send communication regarding well to

Name J. G. GreedenAddress Drawer 4, Wink, Texas

J. G. Greeden  
State Geologist or Oil and Gas Inspector

NEW MEXICO STATE LAND OFFICE  
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST  
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Wink, Texas N. Mex., Aug. 28, 1932

Mr. H. G. Wells

State Geologist,  
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in B. H. Turner  
Well No. 1 in NW/4 of Sec. 34, T. 18S, R. 36E,  
N. M. P. M., Hobbs Oil Field Lea County,  
on September 3, 1932 7-24# lb. casing #s } landed { in Lime  
formation at a depth of Approximately 3970 feet on August 30, 1932 } cemented {  
300 sacks of El Toro Portland cement will be used.

The method used in placing the cement was as follows:

**Halliburton Oil Well Cementing Process under pressure with pumps and plug.**

Fluid level will be bailed to a depth of 3970 feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows: **Shell Petroleum Corporation and  
Mid-West Oil Company**

Additional information:

**Condition of hole is very satisfactory and at total depth of 3500 feet when last survey of hole was taken it showed only 0.2 degree off vertical.**

Approved 19 Sincerely yours,

Except as follows:

**Skelly Oil Company**

Company or Operator.

By

Position

**Division Superintendent**

Send communication regarding well to

Name **J. C. Creeden**

Address **Drawer Q, Wink, Texas**

State Geologist or Oil and Gas Inspector.

NEW MEXICO STATE LAND OFFICE  
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST  
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Wink, Texas

N. Mex., Aug. 28, 1932

Mr. H. G. Wells

State Geologist,  
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in D. E. Turner  
Well No. 1 in N 1/4 of Sec. 34, T. 18S, R. 32E,  
N. M. P. M., Hobbs Oil Field Lee County,  
on September 3, 1932 7-24 lb. casing 4 1/2 } landed { in Line  
formation at a depth of Approximately 5970 feet on August 30, 1932 } cemented {  
800 sacks of El Toro Portland cement will be used.

The method used in placing the cement was as follows:

**Halliburton Oil Well Cementing Process under pressure with pumps and plug.**

Fluid level will be bailed to a depth of 5970 feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows: Shell Petroleum Corporation and  
Mid-West Oil Company

Additional information:

**Condition of hole is very satisfactory and at total depth of 5500 feet when last survey of hole was taken it showed only 0.2 degree off vertical.**

Approved \_\_\_\_\_ 19\_\_\_\_ Sincerely yours,

Except as follows:

**Shell Oil Company**

Company or Operator.

By J. C. Gresham  
Position Division Superintendent

Send communication regarding well to

Name J. C. Gresham

Address Drawer 4, Wink, Texas

State Geologist or Oil and Gas Inspector.

התאחדות המורים והתנועה הליברלית

2012

התורה

1