

## NEW MEXICO STATE LAND OFFICE

SANTA FE, NEW MEXICO

## DEPARTMENT OF THE STATE GEOLOGIST

## OPERATOR'S MONTHLY REPORT OF OPERATIONS

This form must be filled out for all drilling and oil-producing wells and filed with the State Geologist before the 10th of the succeeding month as a regular monthly report, regardless of the status of operations. A separate form is required for each lease. Submit in duplicate.

Mr. H. C. Wells  
State Geologist,  
Santa Fe, New Mexico.

Wink, Texas

N. M.,

Sept. 3,

1932

Dear Sir:

The following is a correct report of drilling and oil producing wells for the month indicated:

If on state land the lease No. is \_\_\_\_\_, Assignment No. is \_\_\_\_\_.

If on patented land the owner is B. E. Turner, Address Hobbs, New Mexico

Month of August, 1932

1/4	Sec.	Twp.	R.	Well No.	IF DRILLING			Pump Depth	Barrels of Oil	Gravity of Oil	Barrels of Water	Barrels Emulsion	Days Well Produced	REMARKS: If Shut Down, State Cause
					Days Operated	Progress For Month	Depth End of Month							
	34	18	30	1	21	Good	3074							
<p>After cementing back to about 500 feet, tools started up on August 2nd and found cement plug at 525 feet. Hole was then re-drilled out in an attempt to make straight hole, which was drilling much better and at 1800 feet in anhydrite a survey showed it to be only 4 degrees off vertical. Hole continued to drill in good shape and at 1975 feet survey made showed it to be less than 1 degree off vertical. The 9" casing was set and cemented with 400 sacks cement at 2780 feet. On August 21st plug was drilled and casing bailed dry in good shape after hole remained open 3 hrs. Survey of hole at 2780 feet showed it to be less than one-half degree off vertical. While drilling at 3074 feet drill pipe twisted off, which it is believed crushed collar of pipe on 9" casing and caused it to part at 3075 feet, leaving 400 feet of drill pipe in hole. After running swedge and fishing tools succeeded in straightening 9" casing up and 4" drill pipe was then fished out. In order to eliminate any further chance of trouble or expense it was decided, since hole was within 40 feet of casing point in lime formation, to run 7" casing at this point. The 7" casing was run with little or no trouble and landed and cemented with 300 sacks cement at 3074 feet. Now shut down waiting on cement set.</p>														
														400 (700)

The production during the month was disposed of as follows:

Pipe lines runs\* .....barrels

Local sales .....barrels

Gasoline plant .....barrels

.....barrels

Total .....barrels

\*Pipe line company.....

Sincerely yours,

**Shelly Oil Company**

By

*J. B. Cauden*

Company or Operator.

Position

**Division Superintendent**

Address

**Drawer 4, Wink, Texas**