

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-07921
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. 16881
7. Lease Name or Unit Agreement Name S. Carter (S/A) Unit Injection Well S.I.
8. Well No. 702
9. Pool name or Wildcat South Carter (San Andres)
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3636 GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> To have been SWD converted to	2. Name of Operator Great Western Drilling Company	3. Address of Operator P.O. BOX 1659	4. Well Location Unit Letter M : 990 Feet From The East South Line and 990 Feet From The West Line Section 5 Township 18S Range 39E NMPM Lea County
---	---	---	---

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1)RIH w/tubing to @ 4640', pump 25 sack cement plug. POH  
2)RIH, perforate 2150' w/4 JS. POH. RIH w/tbg to @ 2050', open bradenhead valve, pump 25 sack cement plug. Pull tbg to 1500', reverse any cement. WOC  
3)RIH & tag plug, repump if necessary. Pull tbg to @ 1008', pump 25 sack cement plug. POH  
4)RIH,perforate 394' w/4 JS. POH. Pump 25 sack cement plug, displace to 294'.WOC  
5)RIH, tag plug @ 294', repump if necessary. Cut off wellhead, pump 10 sack surface plug, erect surface marker.

All sacks to be Class "C" cement. The hole will be circulated w/10# brine containing 25#/salt gel and the cement plugs displaced with the same fluid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gina Howard TITLE Production Tech DATE 11-27-95  
TYPE OR PRINT NAME Gina Howard TELEPHONE NO. (915) 682-5241

(This space for State Use)

APPROVED BY CHIEF ENGINEER LARRY SEXTON TITLE DISTRICT SUPERVISOR DATE NOV 28 1995  
CONDITIONS OF APPROVAL, IF ANY:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF DRILLING OPERATIONS FOR THE C-103 TO BE APPROVED.

dp