

HOBBS EAST SWD WELL F-30

1980' FNL & 2310' FWL

SEC 30-T18S-R39E

DF: 3615'

GL: 3606'

API# 30-025-07950

Circ. to Surface
w/ 900 sx

8 5/8" CSG @ 1883'

100 jts 2 7/8" DuOline tbg
40 jts 2 3/8" IPC tbg

SQZ'D PERFS: 3808'-3834'

SQZ'D PERFS: 3962'-3992'

Circ. to Surface
w/ 1200 sx

TOL @ 4317'

4" Pkr @ 4376'

5 1/2" csg @ 4474'

Perf 4420-4470'

SQZ'D PERFS: 4500' w/100sx

SQZ'D Holes @ 4550, 4830' w/75sx June 2001

TOC orig 5200'

PERFS 5105'-5188': 20 Holes

PERFS 5248'-5261': 12 Holes

25 jts 2 7/8" tbg fish @ 5390'

PERFS 5980'-6054': 25 Holes

PBTD @ 6120'

CIBP @ 6130'

PERFS 6166'-6188'

CIBP @ 6273'

PERFS 6415'-6443'

4" LINER @ 6480'

Drawn	BY
11/15/00	CDH
6/20/01	CDH
11/12/01	CDH
6/25/02	CDH

Perforate San Andres P-1

RICE OPERATING COMPANY

122 West Taylor
Hobbs, NM 88240

Hobbs East SWD F-30

1980' FNL & 2310' FWL
SEC 30, T18S, R39E
Lea County New Mexico