

A blank grid for drawing a picture. The grid is 10 squares wide and 10 squares high. A thick horizontal line runs across the middle, between the 5th and 6th rows. A thick vertical line runs down the middle, between the 5th and 6th columns. This creates four quadrants, each 5 squares wide and 5 squares high. There is a small black dot in the bottom-right quadrant, specifically in the 6th row and 6th column.

SAM K. VIERSEN

(Company or Operator)

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Laney

(Lease)

Well No. 2, in SW 1/4 of SE 1/4, of Sec. 30, T. 18 South, R. 39 East, NMPM.

East Hobbs San Andres

Pool,

Lee

County.

Well is 660 feet from South line and 2,000 feet from East line

of Section 30 If State Land the Oil and Gas Lease No. is _____

Drilling Commenced August 12, 1953, 19..... Drilling was Completed August 28, 19 53

Name of Drilling Contractor.....**Lomax Bros. Drilling Company**.....

Address.....**Midland, Texas**.....

Elevation above sea level at Top of Tubing Head.....**3,606**~~3,606~~

.ZXZXXZXZXZXZXZXZXZXZXZXZXZXZXZXZX..

No. 1, from 4,432' to 4,456' No. 4, from _____ to _____

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from.....to.....feet.

No. 3, from to feet.

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7-5/8"	24#	New	1,797	Baker			
5-1/2"	15.50#	New	4,405	Baker			

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
9-7/8"	7-5/8"	1,797	800			
6-3/4"	5-1/2"	4,405	500			

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.

...Depth Cleaned Out.

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 4456 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

Put to Producing..... **August 28** 19 **53**

OIL WELL: The production during the first 24 hours was.....**496**..... barrels of liquid of which.....**100**..... % was oil;**0**..... % was emulsion;**0**..... % water and..... % was sediment. A.P.I. Gravity.....**33**.....

GAS WELL: The production during the first 24 hours was.....Mcf. per.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southwestern New Mexico

Eastern New Mexico		Southwestern New Mexico	
T. Anhy.....	1840	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	2190	T. Silurian.....	T. Karst Fruitland.....
B. Salt.....	2790	T. Montoya.....	T. Fossiliferous.....
T. Yates.....	3011	T. Simpson.....	T. Bluffs Cliffs.....
T. 7 Rivers.....	3769	T. McKee.....	T. Mescal.....
T. Queen.....	3935	T. Ellenburger.....	T. Pennsylvanian.....
T. Grayburg.....	-	T. Gr. Wash.....	T. Manzano.....
T. San Andres.....	4432	T. Granite.....	T. Gila.....
T. Glorieta.....		T.	T. Mescal.....
T. Drinkard.....		T.	T. Pecos.....
T. Tubbs.....		T.	T.
T. Abo.....		T.	T.
T. Penn.....		T.	T.
T. Miss.....		T.	T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	356	356	Sand & Red Bed				
356	1500	1144	Red Bed				
500	1800	300	Red Bed & Anhydrite				
800	1980	180	Anhydrite & Sand				
980	2060	80	Sand				
060	2715	655	Salt				
715	2890	175	Salt & Potash				
890	3030	140	Salt				
030	3170	140	Anhydrite & gyp				
170	3270	100	Sandy Lime				
270	3290	20	Sand, Lime & gyp				
290	3445	155	Sand, Lime, Anhydrite				
445	3520	75	Sand, Lime & gyp				
520	3709	189	Sand, Lime, Anhydrite				
709	3789	80	Sandy Lime & gyp.				
789	3848	59	Lime, Anhydrite & gyp.				
848	4113	265	Lime & gyp				
113	4145	32	Lime				
145	4178	33	Lime & gyp				
178	4210	32	Lime, gyp & Sandstone				
210	4456	246	Lime				
456			T.D.				

I hereby swear or affirm that the information given herewith is a complete and correct record of the work and all work done on it so far as can be determined from available records.

September 14, 1953

Company or Operator.....**SAM K. VIERSEN**

Address Box 280, Ukmalgee, Oklahoma

Name Sam H. Lewis

Position or Title..... **Partner**