

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

December 27, 1951

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Place

Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Stanolind Oil and Gas Company Pearl Goode Well No. 1 in NE/4  
Company or Operator Lease

of Sec. 31, T -18-S, R 39-E, N. M., P. M., Wildcat Field, Lea County.

N

The well is 1980 feet (N.) (S.) of the N line and 1980 feet  
(W.) (W.) of the E line of Section 31

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is Not Known

Address \_\_\_\_\_


If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Stanolind Oil and Gas Company

Address Box 68 - Hobbs, New Mexico

We propose to drill well with drilling equipment as follows Rotary Tools to



AREA 640 ACRES

LOCATE WELL CORRECTLY  
Total Depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12"	9-5/8"	32.3#	New	500'	Cemented	350 Sacks Circ.
7-7/8"	5-1/2"	14#	New	4500'	Cemented in two stages.*	1st Stage 190 sx. plus 8% gel followed by 100 sx. neat. 2nd Stage - 150 sx

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that (neat the first productive oil or gas sand should occur at a depth of about 4500 feet.

Additional information\* To be two stage cemented with staging collar set at approximately 2000'  
1st Stage - 150% of Theoretical amount to fill to base of salt at a proximately 2900'.  
All indicated pays will be drill stem tested.

Approved \_\_\_\_\_, 19\_\_\_\_

except as follows:

Sincerely yours,

Stanolind Oil and Gas Company  
Company or Operator

By Ralph L. Hendricksen

Position Field Superintendent

Send communications regarding well to

Name Ralph L. Hendricksen


Address Box 68 - Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Yankroge

Title \_\_\_\_\_

2



Sec. 31, TWP. 18S, Rge 39E N.M.P.M.

DRG J. L. S.  
NO