NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	XX		

March 27, 1952 - Hobbs, New Mexico Date Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Skelly Oil Company		Mexico "N"	Well No. 1-A	in the
Company or Operator NE NE of Sec.	32	Lease T. 188	. <u>39Е</u>	, N. M. P. M.,
Unnamed Pool		, 	Lea	County.
The dates of this work were as follows:	March 24,	1952		

Notice of intention to do the work was Kapacon submitted on Form C-102 on March 22, , 1952.

and approval of the proposed plan was (**precision** obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled to a total depth of 6424'. DST 6404-6424'. Recovered 120' GCM and black water, 240' 0&GCM, 60' sulphur water.

Plugged back to 5990' with 150 sacks cement 6424-5980'. DST 5850-5980'. Recovered 4500' sulphur water.

This well was then plugged and abandoned in accordance with the rules and regulations of the New Mexico Oil Conservation Commission.

Well has 8-5/8" OD casing set at 1840' and cement was circulated to surface. The well was plugged by running 100 sacks cement 5980-5670'; mud-laden fluid 5670-4500'; 100 sacks cement 4500-4190'; mud-laden fluid 4190-3200'; 50 sacks cement 3200-3045'; mud-laden fluid 3045-1840'; 25 sacks cement 1840-1790'; set Halliburton DM bridge plug at 1785'; 50 sacks cement 1785-1635'; mud-laden fluid 1635-45'; 15- sacks cement 45' to top; 4" pipe marker installed.

Witnessed by	B. L. Holley Name	Skelly Oil Co. Company	Forenan Title
APPROVED: OIL CONSE	RUATION COMMISSION	I hereby swear or affirm that th is true and correct.	e information given above
Noy yard	wally h Gas inspector Name	Name	mlare
1 Jude is	Gas Inspector Name	Position Dist. Su	pt.
N /	Title		or Operator
	Date 19.		Hobbs, N.N.