MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASS SHUT-OFF	ING	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE F	PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR W	ELL	NOTICE OF INTENTION TO PLUG WELL	XX
NOTICE OF INTENTION TO DEEPEN V	WELL		
		Hobbs, New Mexico March 22	1952
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico			
Gentlemen:			
Following is a notice of intention to do ce	rtain work as	described below at the	
Skelly Oil Company	Mexico	nNn Well No. 1-A in	3072 3.000
of Sec	39E	, N. M. P. M.,	Field
Lea	County.		
		ROPOSED PLAN OF WORK	
FOLLOW INSTRUCTIONS	IN THE RULE	ES AND REGULATIONS OF THE COMMISSION	
and the control of th	sarbuar #		
and the control of th	Suiphur w	T.,6404-6424; Recovered 120; GCM, and ster.	
Plugged back to 5980' with 1 Recovered 4500' sulphur water	50 sacks cor.	cordance with the males and a series	•
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Conser The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840'	surphur was sacks or. well in action Communing 10 cks coment to 3100'	cordance with the males and a series	aden
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Conser The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15 pipe marker installed.	surphur was sacks or. well in action Communing 10 cks coment to 3100'	cordance with the rules and regulation ission. O sacks cement 5980' to 5850',; mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with 5/8" OD casing; Mud laden fluid to nt plug will be run to surface and a	aden
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Consers. The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15 pipe marker installed.	surphur was sacks or. well in action Communing 10 cks coment to 3100'	cordance with the rules and regulation ission. O sacks cement 5980' to 5850', mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with	aden
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Consers. The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15 pipe marker installed.	surphur was sacks or. well in action Communing 10 cks coment to 3100'	cordance with the rules and regulation mission. O sacks cement 5980' to 5850', mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with 5/8" OD casing; Mud laden fluid to nt plug will be run to surface and a Skelly Oil Company Company or Operator By Muliton	aden
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Consers. The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15 pipe marker installed.	surphur was sacks or. well in action Communing 10 cks coment to 3100'	cordance with the rules and regulation mission. O sacks cement 5980' to 5850', mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with 5/8" OD casing; Mud laden fluid to nt plug will be run to surface and a Skelly Oil Company Company or Operator By Position Dist. Supt.	aden I to
Plugged back to 5980' with 1 Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Conser The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15	well in ac wation Com running 10 cks cement to 3100' base of 8 -sack cemen	cordance with the rules and regulation mission. O sacks cement 5980' to 5850',; mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with 5/8" OD casing; Mud laden fluid to not plug will be run to surface and a Skelly Oil Company Company or Operator By Position Dist. Supt. Send communications regarding we	aden I to
Plugged back to 5980' with I Recovered 4500' sulphur water Propose to plug and abandon of the New Mexico Oil Consers. The well will be plugged by fluid 5850' to 4500'; 100 sa 3200; 50 sacks cement 3200' a 50 sack cement plug 1840' approximately 25' where a 15 pipe marker installed. Approved	well in ac wation Com running 10 cks cement to 3100' base of 8 -sack cemen	cordance with the rules and regulation mission. O sacks cement 5980' to 5850', mud 1 4500' to 4300'; mud laden fluid 4300; mud laden fluid 3100' to 1840' with 5/8" OD casing; Mud laden fluid to nt plug will be run to surface and a Skelly Oil Company Company or Operator By Position Dist. Supt.	aden i to